



349.00 EUR

incl. 19% VAT, plus shipping



- Intel® Skylake-U(i5-6200U /i5-6300U), TDP: 15W
 - 2 * SO-DIMM DDR4 Slot up to 32GB
 - Support 1 * 2.5" SATA Device
 - Support 1 * m-SATA SSD Device (Mini PCIe)
 - Support DP / HDMI
 - 1 * Half size Mini PCIe, 1 * Full size Mini PCIe (shared with mSATA)
 - 4 * USB 2.0, 4 * USB 3.0
 - 2 * Intel Gigabit LAN
 - Lockable 12V DC-in Jack
- | | |
|--|---|
| <ul style="list-style-type: none"> • Dimension (W*H*D) • Construction • Colors • MB model • CPU & CHIP • BIOS • Memory • Storage Space | <ul style="list-style-type: none"> • 185 * 142 * 60 mm • Aluminum housing • Black • JBC382F632-6200U-B (i5-6200U) • JBC382F632-6300U-B (i5-6300U) • INTEL® Skylake-U(i5-6200U /i5-6300U), TDP: 15W • AMI 128Mb Flash ROM • 2 * SO-DIMM DDR4 Slot (Max. 32GB) • 1 * 2.5" SATA Device • 1 * m-SATA SSD Device (Mini PCIe) |
|--|---|

- Front I/O Port
 - 2 * USB 2.0
 - 2 * COM
 - 1 * MIC , 1 * Line out

- Rear I/O Port
 - 2 * USB 2.0 , 4 * USB 3.0
 - 1 * DP (max resolution:4096 x 2304@60Hz)
 - 1 * HDMI (max resolution:4096 x 2160@24Hz)
 - 2 * RJ45 (Intel Gigabit LAN)
 - 1 * Line out
 - WiFi (optional / JBC382F632W-6X00U-B)

- Expansion Interface
 - Mini PCIe # 1 : Half-size (for mini PCIe module)
 - Mini PCIe # 2 : Full-size (shared with mSATA)

- Power Source
 - Lockable 12V DC-in Jack
 - Adapter : AC_90~240V / DC_12V_5A / 60W

- Certification
 - EMC : CE , FCC
 - Safety : RoHS , ErP

- Environment
 - Operating Temperature : 0 ~ 50°C
 - Storage Temperature : -20 ~ 70°C

- Mounting
 - Wall mounting Kits

- Packing
 - Net Weight : 2.2KG
 - Gross Weight : 3.5KG
 - Color Box Dimension : 250(W) x 118 (D) x 295 (H) mm