



79.95 EUR

incl. 19% VAT, plus shipping



- Windows 10 Workable support
- ECS Durathon Technology ensure the stability, reliability and performance of system.
- ECS MIB III - A friendly interface for overclocking
- ECS Intelligent EZ Utility : eBLU, eDLU

Supports Intel® CNVi

CPU

Onboard Intel® Gemini Lake processors
1 Phase Thermal Design Power
100% Solid capacitor design

GRAPHICS

Supports DirectX® 12
Supports HDMI 1.4b & Premium Audio
Supports DP 1.2 (only with mainboard version with DP port)

MEMORY

Single-channel DDR4 Memory architecture
Supports DDR4 2400 non-ECC, Un-buffered SDRAM Memory
1 X DDR4 SO-DIMM socket
Support up to 8 GB

| | |
|---------------------------------|---|
| EXPANSION SLOT | 1 X M.2 slot for WiFi/BT PCIe Gen 2 1 X M.2 slot for SSD SATA SSD Support Supports Intel® CNVi |
| Storage | Support by Gimini Lake Express Chipset 2 X Serial ATAIII 6Gb/s |
| Audio | 6-Channel HD audio CODEC Realtek ALC662 Realtek ALC662 6-channel High Definition audio CODEC Meets performance requirements for Microsoft WLP 3.08 Vista premium and mobile PCs Six channel DAC supports 16/20/24-bit PCM format for 5.1 channel audio solution Emulation of 26 sound environments to enhance gaming experience Voice Cancellation and Key Shifting in Karaoke mode Compatible with Direct Sound 3D™, A3D™, I3DL2 |
| LAN | Realtek 8111H Gigabit Fast Ethernet Controller |
| USB | 4 X USB3.1 Gen1 port(s) up to 5Gb/s (either rear I/O or front header) 6 X USB2.0 port(s) Up to 480 Mb/s [Back Panel 2 port(s), Onboard 4 port(s)] |
| REAR PANEL I/O | 1 X PS/2 Keyboard & PS/2 mouse connectors 1 X Audio port (Line Out/Line In/Mic In) 1 X RJ-45 port 1 X HDMI port(s) 1 X D-Sub (VGA) port(s) 1 X Display port(optional instead of D-SUB (VGA)) 1 X DC-in 19V Connector |
| CONNECTORS & HEADERS | 1 X 4-pin SYS_FAN connector 1 X Front Panel MIC/Speaker out header 1 X Front Panel switch/LED header 2 X USB 2.0 header 1 X CLR_CMOS header 2 X Serial port header (COM) 1 X Parallel port header (LPT) 1 X eDP header (optional) |
| SYSTEM BIOS | AMI BIOS with 128 MB SPI Flash ROM Supports M.I.B III Utility Dual Display Support GUI UEFI BIOS Multi-Language BIOS |
| FORM FACTOR | Mini ITX Form Factor 170*170 |
| OS Support | Windows 10 64-bit Windows 10 32-bit |
| Certifications | CE/FCC Certification WHQL Certification |

Bundled Software

ECS Intelligent EZ Utility : eBLU, eDLU