



999.00 EUR

incl. 19% VAT, plus shipping



- Applied Solid Capacitor for CPU VRM to ensure a longer lifespan for system
- ECS Durathon Technology ensure the stability, reliability and performance of system.
- Dual Display design for multiple output support
- Integrated Printer (LPT) port / header to expand functionality
- Microsoft Windows 8 Certified
- Intel® VRD 12 Ready
- Supports DirectX® 11 to enhance graphical performance
- Supports HDMI 1.4a Technology (resolution up to 1920X1200) and HDCP function
- Free Bundle: CyberLink Media Suite

Supports Intel® CNVi

CPU

Onboard Intel® Bay Trail processors
 On-Board CPU Intel® Bay Trail J1900 processor
 VRD 12.0
 Solid Capacitor for CPU side
 Supports Intel® Hyper-Threading Technology

GRAPHICS

Supports DirectX® 11
 Supports Full HD 1080P Blu-ray / HD-DVD
 Playback

MEMORY	<p>Single-channel DDR3 Memory architecture 1 X DDR3 SO-DIMM socket Support up to 8 GB</p>
EXPANSION SLOT	<p>1 X Mini PCI Express X1 slot(s) for Wi-Fi / Bluetooth modules</p>
Storage	<p>2 X Serial ATAIII 3Gb/s</p>
Audio	<p>6-Channel HD audio CODEC Realtek ALC662 Realtek ALC662 6-channel High Definition audio CODEC Meets performance requirements for Microsoft WLP 3.08 Vista premium and mobile PCs Six channel DAC supports 16/20/24-bit PCM format for 5.1 channel audio solution Emulation of 26 sound environments to enhance gaming experience Voice Cancellation and Key Shifting in Karaoke mode Compatible with Direct Sound 3D™, A3D™, I3DL2</p>
LAN	<p>Realtek RTL8111G Gigabit Fast Ethernet Controller</p>
USB	<p>1 X USB3.1 Gen1 port(s) up to 5Gb/s 8 X USB2.0 port(s) Up to 480 Mb/s (Back Panel 4 port(s), Onboard 4 port(s))</p>
REAR PANEL I/O	<p>1 X PS/2 Keyboard & PS/2 mouse connectors 1 X Audio port (Line Out/Line In/Mic In) 1 X RJ-45 port 1 X HDMI port(s) 1 X D-Sub (VGA) port(s) 1 X USB3.1 Gen1 port(s) 4 X USB2.0 port(s) 1x DC-In connector</p>
CONNECTORS & HEADERS	<p>1 X 4-pin CPU_FAN connector with smart fan 1 X 4-pin SYS_FAN connector with smart fan 1 X Front Panel MIC/Speaker out header 1 X Front Panel switch/LED header 1 X USB 2.0 header (Support additional 2 USB ports) 2 X SATA II 3Gb/s connector(s) 1 X CLR_CMOS header 2 X Serial port header (COM) 1 X Parallel port header (LPT) 1 X LVDS connector (optional)</p>

SYSTEM BIOS

AMI BIOS with 8 MB SPI Flash ROM
Supports ACPI 5.0 & DMI
Dual Display
Plug and Play, STR (S3) / STD (S4) , Hardware
monitor, Multi Boot
Multi-Language BIOS
Audio, LAN, can be disabled in BIOS
Dual-Monitor function

FORM FACTOR

Mini ITX Form Factor 170*170

OS Support

Windows 7 64-bit
Windows 8.1 32-bit
Windows 8.1 64-bit
Windows 10 64-bit
Windows 10 32-bit

Certifications

CE/FCC Certification
ErP/EuP Certification
WHQL Certification
WHCK Certification