


98.95 EUR

incl. 19% VAT, plus shipping

- **Industrial Arduino IDE !**
- **Built-in OLED Display !**
- **Flexible programming !**
- **8Mhz CPU !**



Support:  [Datasheet](#) |  [Brochure](#) |  [Quick Start](#) | [Applications](#)

NORVI Cema Industrial Arduino is the most compact version of NORVI series. Yet it has 8 Outputs and 8 Inputs, beating all the devices of same size on the market. Two transistor outputs of it adds PWM or Pulse output capabilities. It comes with a 6 pin expansion port with Serial output. Cema is leading with reliability in the industrial environments.

- 8x Sink/Source Digital Inputs (24V)
- 6x 5A Relay Outputs
- 2x Open collector Transistor
- Programmable with Arduino IDE
- Intergrated OLED and buttons programmable as HMI
- LED indicators for easy diagnosis

Range of product	NORVI CEMA
Product type	Programmable Controller
Rated supply voltage	24V DC
Discrete input number	8 discrete input
Discrete output type	Relay and Transistor
Discrete output number	6 Relay outputs, 2 Transistor outputs
Discrete output voltage	24V DC for transistor output
Discrete output current	0.5A with T0.0... T0.1 Transistor 2 A with R0....R5
Complementary	
Discrete IO number	16
Number of Expansions	-----
Supply voltage limits	20.4 28.8V
Inrush current	<= 50A
Power consumption in W	32.6 40.4 with all outputs ON
Discrete logic Input	Sink or source
Discrete input Voltage	24V DC
Voltage TypeVoltage state 1	> = 15V for Input
Voltage TypeVoltage state 0	< = 5V for input
Discrete Input Current	5mA for Input
Input impedance	4.7k Ohm for Input
Local signalling	1 LED green for PWR 1 LED green for RUN 8 LED green for I0.....I7 6 LED green for R0.....R5 2 LED green for T0....T1
Electrical connection	Removable screw terminal block for inputs and outputs (pitch 5.08 mm)
Mounting support	Top hat type TH35-15 rail conforming to IEC 60715 Top hat type TH35-7.5 rail conforming to IEC 60715 Plate or panel with fixing kit
Height	90.50 mm
Depth	56.60 mm
Width	60.60 mm
Weight	0.43 kg
Environment	
Resistance to electrostatic discharge	4kV on contact, 8kV on air

Resistance to electro magnetic fields

10 V/m (80 MHz 1 Ghz)

3 V/m (1.4 MHz 2 GHz)

1 V/m (2 MHz 3 GHz)

Immunity to microbreaks

10 ms

Relative humidity

10...95% without condensation in operation

IP degree of protection

IP20

Operating altitude

0...2000m

Storage altitude

0...3000m

Shock resistance

15 gn for 11 ms

Resistance to electrostatic discharge

4kV on contact, 8kV on air

Resistance to electro magnetic fields

10 V/m (80 MHz 1 Ghz)

3 V/m (1.4 MHz 2 GHz)

1 V/m (2 MHz 3 GHz)