

999.00 EUR

incl. 19% VAT, plus shipping



- Intel® Apollo Lake SoC Processor
- 1\* DDR3L 1866MHz SODIMM up to 8 GB
- 4\* USB3.1, 2\* HDMI, 2\* RJ45, 1\* MIC/Line-out Combo, 1\* COM (RJ45 type)
- Operating Temperature: -40 ~ 70° C
- M/B Form Factor : uTX (117x112mm)
- DC-12V\_60W Adapter

MB Model	- MT95-90
Part No.	- HBFCT95-90B - HBFCT95W-90B (WIFI)
BIOS	- AMI Flash ROM
CPU/Chipset	- Intel® Apollo Lake SoC Processor (E3940 CPU TDP 9.5W)

Memory	- 1* DDR3L 1866MHz SO-DIMM up to 8 GB
Network	- 2* Intel® i210AT GbE
Storage	- 1* M.2 M-key (2242) Support SATA interface
Expansion	- 1* M.2 E-key (2230) Support USB2.0 & PCIe1 interface (for WiFi module installed) - 1* M.2 B-key (3042) Support USB3.0 interface (for 3G/4G/5G module installed)
Rear Panel I/O	- 2* USB3.1 (Gen1) - 2* HDMI (Max. Resolution: 3840 x 2160@30Hz) - 2* RJ45 - 1* MIC/Line-out Combo (Realtek® ALC662VD) - 1* COM (RJ45 type) - 2* Antenna holes (WiFi only) - 1* DC-in jack (Lockable type)
Front Panel I/O	- 1* Power button - 1* Power LED, 1* HDD LED, 2* LAN LED - 2* USB3.1 (Gen1) - 1* AT / ATX mode Switch
Power Source	- AC to DC Adapter / AC 90~240V_DC12V_5A_60W - MT95-90 MB_DC 12V input
Compliance	- CE, FCC, LVD, RoHS, ErP Ready
Temperature	- Operating Temperature: -40 ~ 70° C (Under the condition of using M.2 interface SSD) (The test environment is closed and windless) - Storage Temperature: -40 ~ 80° C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
Dimensions	- 144 (W) x 116.9 (D) x 65 (H) mm
OS Support	- Windows 10, Linux