

20.00 EUR

incl. 19% VAT, plus shipping



- Intel Apollo Lake-I SoC Processor (Default: E3940)
- Support 1* SO-DIMM DDR3L-1866MHz up to 8GB
- All-aluminum body, produced by casting process
- Operating Temperature: -40 ~ 70°C
- 9~36V DC-in (Phoenix terminal connector)

| | |
|-------------|---|
| MB Model | – JNF951T-E3940 |
| Model No. | – HBJC386F951T-3940B – HBJC386F951TW-3940B (WIFI) |
| BIOS | – AMI Flash ROM |
| CPU/Chipset | – Intel® Apollo Lake-I SoC Processor (Default: E3940) |

| | |
|-----------------|--|
| Memory | – 1* SO-DIMM slots DDR3L-1866MHz up to 8GB |
| Storage | – 1* M.2 (M-key 2280) slot for SSD |
| Network | – 2* Intel i210-IT GbE – 1* Full-size mini-PCIE slot |
| Rear Panel I/O | – 4* USB3.0 – 2* RJ45 – 1* VGA (Max. Resolution: 1920×1200@60Hz) – 1* HDMI (Max. Resolution: 3840×2160@30Hz) – 1* Line out – 2* WIFI Antenna (HBJC386F951TW-3940B only) – 1* DC-in (3 Pin Phoenix terminal) |
| Front Panel I/O | – 1* Power SW + Power LED – 1* ATX & AT mode Switch – 1* SIM Card slot – 2* COM (RS232/422/485_ COM1 w/power) – 1* Power SW (2 PIN out) – 1* 16 bit GPIO (8-IN, 8-OUT, Isolation Protection 2,500VDC, Output Voltage 5~20VDC) – 2* RS485 (Isolation Protection 2,500VDC) |
| Power Source | – Adapter: AC 90~240V input / DC12V-5A-60W – MB: Support 9~36V DC-in |
| Compliance | – CE, FCC, LVD, RoHS, ErP Ready |
| Temperature | – Operating Temperature: -40 ~ 70° C (Under the condition of using M.2 interface SSD) (The test environment is closed and windless) – Storage Temperature: -40 ~ 80° C – Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| Dimensions | – 185 (W) x 142 (D) x 60 (H) mm |
| Packing | – Net Weight: 2.2KG – Gross Weight: 3.5KG – Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm |