



999.00 EUR

incl. 19% VAT, plus shipping

- **Perfect as router !**
- **6x Intel Gigabit LAN !**
- **Intel Quad Core CPU !**
- **FANLESS !**



Limited offer. As long as stock lasts !

With pre-installed mSATA SSD 32GB (MEMXPRO M3B mSATA SSD 32GB (MB3MB0132G025SN)) and 8GB RAM (DIMM SO-DDR-3 8GB [Low Voltage, 1.35V] (Crucial CT102464BF160B.M16FN)) !

Excellent as a router. 6x Intel i211AT Gigabit LAN connections, high NAT performance thanks to Intel 2Ghz Quad-Core Celeron CPU, 3G / 4G / LTE / 5G modem or WLAN upgradeable via mini-PCIe slot. 1x COM port (RS232 / 422/485) and optionally 4x more can be retrofitted. Fanless, small, energy efficient, strong!

- Fanless Intel Celeron Bay Trail J1900 SoC Processor
- 6 \* Intel Gigabit LAN Ports
- Optional: Add 4 \* COM Ports (PN# ADPIECOM4)
- ECO-design for EuP/ErP

Scope of supply : Jetway JBC390F541XA-19-B (32GB SSD/8GB RAM), 12V 60W AC/DC power adapter with power cord, screws, 2x DIN Rail mounting adapter, Driver CD, manual, 2x metal mounting adapter

Specification

<b>Model Name</b>	<b>JBC390F541XA-1900-B</b>
<b>Part Number</b>	<b>HBJC390F541XA19B</b>
<b>Motherboard Specification</b>	
<b>CPU</b>	Intel® Celeron J1900, 2.0GHz Quad-Core SoC, 10W, Bay Trail
<b>Memory</b>	1 * 204-pin DDR3L-1333 SO-DIMM up to 8GB (1.35V required)
<b>Graphics</b>	Intel HD Graphics
<b>LAN</b>	6 * Intel i211AT Gigabit LAN
<b>Audio</b>	Realtek ALC662 HD Audio
<b>Storage</b>	1 * 2.5" SATA2 3Gb/s drive bay for HDD or SSD 1 * mSATA/mini-PCI Express shared slot (Full-size)
<b>Wireless / Mini-PCIE Slot</b>	1 * Mini-PCI Express slot (Full-size)
<b>USB / SIM</b>	Embedded 1 * USB 3.0 and 3 * USB 2.0, 1 * SIM card socket
<b>Chassis Specification</b>	
<b>Product size</b>	185 (W) * 165 (D) * 48 (H) mm
<b>Color</b>	Black
<b>Storage Bay</b>	1 * 2.5" Drive Bay (Only support SATA 2.5" HDD or SSD)
<b>Front I/O Port</b>	1 * Power Button 1 * HDD LED 4 * RJ-45 LAN ports
<b>Rear I/O Port</b>	1 * +12V DC-in jack 1 * Reset Switch 1 * USB 3.0 ports 3 * USB 2.0 ports 1 * HDMI 2 * RJ-45 LAN ports 1 * Serial port (RS232/422/485) 1 * VGA port 1 * Line Out jack 1 * MIC In jack 2 * holes for SMA pigtail Connectors for WiFi Antenna
<b>Environment</b>	Operating Temperature : 0 ~ 40°C Storage Temperature : -20 ~ 85°C
<b>Functional</b>	Networking Appliance, Firewall/Router, Industrial Control, Digital Security, Embedded System
<b>Certificate</b>	CE,FCC,ErP For Barebone CE,FCC,TUV,UL,CCC,CB,ErP For Power Adapter