

598.00 EUR

incl. 19% VAT, plus shipping

- **9-36V DC-in !**
- **ARM Cortex RK3288 !**
- **Android 5.1/9.0, Debian 9.0 !**
- **IP65 Front !**



- 10.1" 350 nits TFT LCD with LED backlight
- ARM Cortex RK3288 CPU, 4x 1,8 GHz
- Onboard 1333/2GB DDR3L DRAM
- Onboard 8G Flash ROM
- Support Android 5.1/9.0 or Debian 9.0
- Front IP65 for protection against water and dust
- Support 9-36V DC-in

Display	<ul style="list-style-type: none"> <li>- IP65, NEMA 4 rugged protection, metal front bezel</li> <li>- 10.1" With LED Backlight</li> <li>- 350 nits Brightness (cd/m<sup>2</sup>)</li> <li>- 262K display color</li> <li>- 1280 x 800 @ 60Hz resolution</li> <li>- 160°/160° viewing angle (H/V)</li> <li>- 0.1695 x 0.1695mm pixel pitch</li> <li>- 16:10 aspect ratio</li> <li>- 600:1 contrast ratio</li> <li>- 25ms response time</li> </ul>
Touch Screen	<ul style="list-style-type: none"> <li>- Projected capacitive type</li> <li>- 257.10 x 159.66mm ±0.2mm active range</li> <li>- Transparency ≥ 87%</li> <li>- Operating force ≤ 80g</li> <li>- Surface Hardness ≥ 6H (ASTM D3363, pressure 1N/45°)</li> </ul>
Case	<ul style="list-style-type: none"> <li>- Aluminum panel</li> <li>- Iron case</li> <li>- Black color</li> <li>- Spray paint coating requirement</li> </ul>
Main System	<ul style="list-style-type: none"> <li>- Rockchip® ARM Cortex A17 1.8GHz/QC processor</li> <li>- Onboard 1333/2GB DDR3L DRAM</li> <li>- Onboard 8G Flash ROM</li> <li>- Watchdog Timer 256 levels, 0~255 sec.</li> <li>- Speaker: 2* 2W/8Ohm</li> <li>- Camera: 1* 500W USB (Option)</li> <li>- OS Support Android 5.1/9.0 or Debian 9.0</li> <li>- Power Consumption: 8.5W</li> </ul>
Expansion	<ul style="list-style-type: none"> <li>- 1* Micro SD socket</li> </ul>
I/O Connector	<ul style="list-style-type: none"> <li>- 2* USB2.0 (USB1 Co-lay OTG)</li> <li>- 1* HDMI 1.4</li> <li>- 1* AUDIO(Line-out +MIC)</li> <li>- 1* Micro SD Socket</li> <li>- 1* Power Button</li> <li>- 1* GbE</li> <li>- 1* 9~36V DC jack</li> </ul>
Power Input	<ul style="list-style-type: none"> <li>- 9~36V DC-in</li> </ul>

Dimensions	- 259.3 * 177.3 * 39.0mm
Compliance	- CE, FCC, IP65(Front)-Option
Safety	- Shock: 15G, 11ms duration - Vibration: 5~500Hz/1 Grms
Temperature	- Operating: -10°C ~ 50°C - Storage: -20°C ~ 60°C