



369.00 EUR

incl. 19% VAT, plus shipping

- Intel® Apollo Lake SoC Processor
- Support 1* DDR3L 1866MHz SO-DIMM up to 8GB
- 1* VGA, 2* HDMI
- 4* USB3.0, 1* RS232/422/485, 2* GbE, 1* Audio
- 12V DC-in

MB Model	- JNU691B-3455
Part No.	- HBFBU691-3455-B - HBFBU691Z-3455-B (support Mini PCIe ac WiFi)
BIOS	- AMI UEFI
CPU/Chipset	- Intel® Apollo Lake J3455 SoC Processor (Quad Core, 1.50/2.30 GHz)
Memory	- Support 1 * DDR3L 1866MHz SO-DIMM up to 8GB

Network	<ul style="list-style-type: none"> - 2 * RJ45 (Realtek RTL8111H GbE) - Mini PCIe ac Wifi card (HBFBU691Z-3455-B only)
Storage	<ul style="list-style-type: none"> - Support 1 * mSATA (full size) Device
Expansion	<ul style="list-style-type: none"> - 1 * half size Mini PCIe slot for WiFi module
Audio	<ul style="list-style-type: none"> - HD Audio: Realtek ALC662VD
Rear Panel I/O	<ul style="list-style-type: none"> - 2 * USB 3.0 - 2 * HDMI (Max. resolution: 3840×2160@30Hz) - 2 * GbE - 1 * GND hold - 1 * Line-out/MIC combo - 1 * DC-in jack
Front Panel I/O	<ul style="list-style-type: none"> - 1 * VGA (Max. resolution: 1920×1200@60Hz) - 2 * USB 3.0 - 1 * COM (RS232/422/485) - 1 * power button
Power Source	<ul style="list-style-type: none"> - Adapter : AC 90~240V / DC12V / 40W - MB : 12V DC input
Compliance	<ul style="list-style-type: none"> - CE, FCC, RoHS, ErP
Temperature	<ul style="list-style-type: none"> - Operating Temperature: 0 ~ 50° C with air flow (mSATA) - Storage Temperature: -10 ~ 70° C - Humidity : 90%, non-condensing
Dimensions	<ul style="list-style-type: none"> - 124(W) x 109 (D) x 55 (H) mm