



999.00 EUR

incl. 19% VAT, plus shipping

- **VGA/HDMI Dual !**
- **9-24VDC !**
- **2x MiniPCIe !**
- **2x COM !**

Support:  [Specifications](#) |  [Manual \[EN\]](#)

Limited offer. As long as stock lasts !

Excellent as a router. 2x Intel WG82574L Gigabit LAN connections, high NAT performance thanks to Intel 1.86Ghz Dual-Core Atom CPU, 3G / 4G / LTE / 5G modem or WLAN upgradeable via 2x mini-PCIe slot. 2x COM port. Fanless, small, energy efficient, strong!

Scope of supply : DFI EC800-CD2041 (2GB RAM/16GB SSD), 12V 60W AC/DC power adapter with power cord, 2x metal mounting adapter

CPU

Intel® Atom™ D2550, 1.86GHz, 2x 512K L2, 10W TDP, dual-core

Chipset

Intel® NM10 Express Chipset

RAM

2GB DDR3 onboard

Graphics

Intel® GMA 3650

- 1 VGA port supports display resolution up to 1920x1200
- 1 micro HDMI port supports display resolution up to 1920x1080
- Smooth Video Playback - Supports hardware decoders (H.264, VC-1, MPEG-4) with Full HD 1080p video playback capability

Storage	<ul style="list-style-type: none"> • 1 CFAST socket • 1 mSATA module via a Mini PCIe slot (16GB Module included)
Ethernet	2x Intel® WG82574L Gigabit Ethernet controllers (DUAL LAN)
Audio	<ul style="list-style-type: none"> • Realtek® ALC886 7.1-channel High Definition Audio • 1 line-out and 1 mic-in
COM	<ul style="list-style-type: none"> • 2 DB-9 ports (RS232/422/485) • Supports RS485 auto direction control
Expansion	<ul style="list-style-type: none"> • 3 Mini PCIe slots - 2 slots for communication : One slot supports PCIe x1, USB, and LPC signals for Wi-Fi module or LPC module : One slot supports PCIe x1, USB, and 3G signals for 3G or GPRS module - 1 slot for storage : Supports mSATA module • 1 SIM card socket • 1 CFAST
Front I/O	<ul style="list-style-type: none"> • 1 DB-9 RS232/422/485 COM • 1 mic-in • 2 LAN • 4 USB 2.0 (Type A) • 1 CFAST socket • 1 status LED • 1 hdd LED • 1 reset button • 1 power button with LED
Power	9~24V DC power input voltage
Environment	<ul style="list-style-type: none"> • Temperature - Operating: 0oC ~ 60oC - Storage: -40oC ~ 80oC • Humidity - Operating: 10% to 85% non-condensing - Storage: 10% to 90% non-condensing
Construction	Aluminium
Mounting	Wall/VESA/DIN Rail mount
Dimensions	161mm x 32mm x 108.2mm (W x H x D)
Weight	700g
OS Support	<ul style="list-style-type: none"> • Windows XP, WES 2009, POSReady 2009 • Windows 7 (32-bit), WES 7 (32-bit) • Linux
Other features	Watchdog Timer function
Certification	<ul style="list-style-type: none"> • CE • FCC Class A • RoHS • UL • CCC • KC