



9999.00 EUR

incl. 19% VAT, plus shipping

- **Intel Coffee Lake !**
- **Barebone !**
- **12-36V DC-in !**
- **4x HDMI / 2x DP !**



- Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor (Max 35W)
- Intel® Coffee Lake-S H310 Chip
- Support Dual Channel DDR4 2133MHz up to 32GB
- Support MXM Type A/B VGA Card(Type A or B, Max 75W)
- 1* M.2 E key Support CNVi, 1* M.2 B key Support 3G/4G Module
- 2* RS232 (COM1/2 Support 5V/12V TTL), 4* USB3.1, 4* USB2.0, 1* GbE, 4* HDMI, 2* DP, 1* eDP (By MXM)
- 12~36V DC-in

MB Model	- JNC9AMXM-H310
Part No.	- HBJC909C9A

BIOS	- AMI 128MB SMT Flash ROM
CPU/Chipset	- Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor (Max 35W) - Intel® Coffee Lake-S H310 Chip
Memory	- 2* DDR42133MHz up to 32GB
Network	- 1* Intel® I219LM GbE
Storage	- 1* 2.5" SATA 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm) - 1* M.2 M Key Socket (2280, Support NVMe)
Rear Panel I/O	- 4* USB3.1 - 2* DP (Up: DP By CPU, Bottom: DP By MXM VGA Card) - 4* HDMI (2* EXT HDMI By MXM, INT HDMI2 BY MXM, INT HDMI1 By CPU) - 1* RJ45 - 1* RS232 - 1* Line-out, MIC - 1* DC Jack - 1* Power Button
Internal Connector	- 1* M.2 B Key Socket for 3G/4G Module - 1* M.2 E Key Socket for CNVi or PCI-E/USB WIFI/BT
Power Source	- DC 12~36V input
Compliance	- CE, FCC, RoHS, ErP Ready (Option)
Temperature	- Operating Temperature: -10 ~ 50° C - Storage Temperature: -20 ~ 60° C
Dimensions	- 279.8 (W) x 224.0 (D) x 115.9 (H) mm
OS Support	- Windows 10, Linux