



489.00 EUR

incl. 19% VAT, plus shipping

- **Jetson Nano !**
- **2x USB 3.0 !**
- **NVIDIA !**

**Support:**  [Datasheet](#) |  [Manual](#)

AVerMedia AVerAI Box PC NO111B equips NVIDIA® Jetson Nano™ module (version B01) and is designed for the industry applications in the environment with the high physical space concern and operation in the temperature range from 0°C to 60°C. It features the very compact dimensions of 91.4mm x 76.6mm x 70mm.

AVerAI NO111B can provide the access to a list of rich I/O functions, which includes 2x 2 Lane MIPI CSI-2, 1x 4 Lane MIPI CSI-2 MIPI Camera Input (internal), 1x 4Kp60 HDMI output, 2x USB 3.0, 1x GbE RJ-45, 20-pins expansion header (internal), 1x Micro SD card slot, and 1x Micro-B USB 2.0 for recovery.

With the compact dimensions, design for reliable field installation, and the rich I/O functions, NO111B is the best cost-effective choice for AIoT edge computing in the intelligent video analytics applications of Smart Retail, Smart Camera, Smart Medical and Smart City.

- Embedded NVIDIA® Jetson Nano™ module (version B01)
- 1x GbE, 2x USB 3.0, 1x 4Kp60 HDMI outputs
- Internal 20-pin expansion header

- 1x micro-SD card slot
- Operating temperature: 0°C ~ 60°C
- Dimension: 91.4mm x 76.6mm x 70mm

<b>Model</b>	<b>NO111B</b>
<b>Type</b>	<b>Box PC</b>
<b>NVIDIA GPU SoC Module Compatibility</b>	<b>NVIDIA® Jetson Nano™ module (version B01)</b>
<b>Networking</b>	<b>1x GbE RJ-45</b>
<b>Display Output</b>	<b>3840 x 2160 at 60Hz</b>
<b>Temperature</b>	<p><b>Operating temperature 0°C~60°C</b></p> <p><b>Storage temperature -40°C ~ 85°C</b></p> <p><b>Relative humidity 40 °C @ 95%, Non-Condensing</b></p>
<b>MIPI Camera Inputs(Internal)</b>	<ul style="list-style-type: none"> <li>• <b>2x 2 lane MIPI CSI-2, 15 pin FPC 1mm Pitch Connector (Compatible on NVIDIA® Jetson Nano™ Developer Kit)</b></li> <li>• <b>Optional: 1x 4 lane MIPI CSI-2, 36 pin FPC 0.5mm Pitch Connector</b></li> </ul>
<b>USB</b>	<p><b>1x USB 2.0 Micro-B for recovery</b></p> <p><b>2x USB 3.0 Type-A</b></p>
<b>Storage</b>	<b>1x micro-SD card slot</b>
<b>GPIO Expansion (Internal)</b>	<b>20 pins: 2x I2C, 1x UART, 9x GPIOs</b>
<b>Input Power</b>	<p><b>12V/5A</b></p> <p><b>9V~19V is recommended.</b></p>

**Power Cord**

**US/JP/EU/UK/TW**

**Fan Module**

**Heat sink with fan**

**Buttons**

**Power and Recovery**

**RTC Battery**

**Support RTC battery and Battery Life  
Monitoring by MCU**

**PCB/Electronics Mechanical Info**

**W: 91.4mm x L: 76.6mm x H: 70mm (3.60" x  
3.02" x 2.76")**

**Weight: 480g**

**Certifications**

**CE, FCC**