




498.00 EUR

incl. 19% VAT, plus shipping



- Intel® Apollo Lake SoC Processor (Default: J3455)
- Support 1 * SO-DIMM DDR3L-1866MHz up to 8GB
- All-aluminum body, produced by casting process
- Support Wide Voltage 9~36V DC-in

MB Model	<ul style="list-style-type: none"> - MF94-00B (J3455 CPU_10W, Default) - MF94-02B (J3455 CPU_10W, TPM2.0) - MF94-90B (E3940 CPU_9.5W) - MF94-92B (E3940 CPU_9.5W, TPM2.0) 		
Part No	Non-Wifi	Mini PCIe ac WiFi card	TPM2.0
	<ul style="list-style-type: none"> - HBFDF94-00B (Default) - HBFDF94-90B 	<ul style="list-style-type: none"> - HBFDF94Z-00B - HBFDF94Z-90B 	<ul style="list-style-type: none"> - HBFDF94-92B - HBFDF94Z-92B

BIOS	- AMI Flash ROM
CPU/Chipset	- Intel® Apollo Lake SoC Processor (Default: J3455, TDP 10W)
Memory	- 1* SO-DIMM slots DDR3L-1866MHz up to 8GB
Network	- 2* Intel® GbE (I211-AT)
Storage	- 1* M.2 M-key 2242 slot for SSD - 1* 2.5" Drive
Expansion	- 1* Full size Mini PCIe slot (USB2.0/PCIex1) - 1* M.2 B-key 3042 slot (USB3.0/PCIex1)
Rear Panel I/O	- 2* RJ45 - 1* HDMI (Max. Resolution: 3840×2160@ 30Hz) - 1* SIM Card slot - 1* Line-out - 1* DC-in (9~36V) - 1* USB2.0 - 3* USB3.1 (Gen.1)
Front Panel I/O	- 1* Power SW, 1* Reset - 1* Power LED, 1* HDD LED - 1* MIC - 1* Line-out - 2* COM (COM1 support RS485) - 2* USB2.0
Power Source	- Adapter / AC 90~240V input / DC19V-90W - MB: support 9~36V DC-in
Compliance	- CE, FCC, LVD, RoHS, ErP Ready
Temperature	Operating Temperature: - J3455 CPU : HBFDF94-00B / HBFDF94Z-00B: 0 ~ 50° C - E3940 CPU : HBFDF94-90B / HBFDF94Z-90B / HBFDF94-92B / HBFDF94Z-92B: -40 ~ 70° C - Storage Temperature: -20 ~ 85° C - Humidity: 90%, non-condensing

Dimensions	- 193 (W) x 142.4 (D) x 62 (H) mm
OS Support	- Windows 10, Linux
Warranty	- 2 Years limited warranty
Packing	- Net Weight: 2.2KG - Gross Weight: 3.5KG - Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm