



279.00 EUR

incl. 19% VAT, plus shipping

- **LGA1150 !**
- **6x COM !**
- **2x LAN !**
- **Micro ATX Format !**



Support:  [Datasheet](#)

- Intel® LGA1150 Socket support 4th Gen. Core Processor (Max. 90W)
- Intel® Lynx Point H81 Chip
- 2* DDR3/DDR3L 1600/1333MHz up to 16GB
- Realtek HD Audio
- 1* Intel®i217LM GbE, 1* Intel® i211AT GbE
- 4* SATA, 1* M.2 (M key), 1* PCIe x16, 1* PClex4, 1*PCIe x1, 4* PCI
- 1* VGA, 2* HDMI
- 2* RS232/422/485 (COM1/2), 4* RS232, 2* USB3.0, 7* USB2.0
- ATX Power Input
- ATX Form Factor (305 *220 mm)

Model	<ul style="list-style-type: none"> – JLA1H-00 – JLA1H-0A (Without Audio function)
Form Factor	– ATX (305 * 220mm)

Processor System	<ul style="list-style-type: none"> – Intel® LGA1150 Socket supports 4th Gen. Core Processor (Max. 90W) – Intel® H81 Express chipset – AMI 32Mb Flash ROM BIOS
Expansion Slot	<ul style="list-style-type: none"> – 1* M.2 (M-key, 2242/2280, SATA Interface, CO-lay SATA4) – 1* Mini PCIe, full size (USB2.0 interface) – 4* SATA4 (Co-lay M.2) – 1* PCIe x16 + 1* PCIe x4 slot or 1* PCe x6 + 2* PCIe x1 slot – 4* PCI slots
Memory	<ul style="list-style-type: none"> – 2* LONG DIMM DDR3/DDR3L 1600/1333MHz DRAM up to 16GB
Graphics	<ul style="list-style-type: none"> – Intel® HD Graphics, shared memory – 1* VGA (Max Resolution: 1920×1200@60Hz) – 2* HDMI 1.4 (Max Resolution: 2560×1600@60Hz) – Support Dual Displays
Ethernet	<ul style="list-style-type: none"> – 1* Intel i217LM GbE – 1* Intel i211AT GbE
Audio	<ul style="list-style-type: none"> – HD audio: Realtek codec (JLA1H-00)
SATA	<ul style="list-style-type: none"> – 2* SATAIII (6.0Gb/s) – 2* SATAII (3.6Gb/s)
Rear I/O	<ul style="list-style-type: none"> – 1* VGA – 2* HDMI – 2* RJ45 – 2* USB3.0 – 4* USB2.0 – Line-in, Line-out, MIC – 2* RS232/422/485 (support 5/12V TTL) – 1* PS/2

Internal I/O	<ul style="list-style-type: none"> - 2* USB 2.0 - 1* USB2.0 (Erect) - 4* RS232 (COM3/4 support 5/12V TTL) - 1* Parallel (Co-lay GPIO) - 1* GPIO (16 bit, Co-lay Parallel) - 1* SIM Card slot - 1* Chassis intrusion - 1* Audio Header - 1* SMBUS / I2C - 1* AT mode - 1* TPM2.0 (option)
Watchdog Timer	<ul style="list-style-type: none"> - From Super I/O to drag RESETCON# - 256 segments (10sec ~ 255min)
Power	<p>ATX PWR, AT/ATX Supported</p> <ul style="list-style-type: none"> - AT: Directly PWR on as Power input ready - ATX: Press Button to PWR on after Power input ready
Compliance	<ul style="list-style-type: none"> - CE, FCC, RoHS, REACH
Temperature	<ul style="list-style-type: none"> - Operating: 0°C ~ 60°C - Storage: -20°C ~ 70°C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none"> - Windows 7, 8, 10, Linux