

539.00 EUR

incl. 19% VAT, plus shipping



- **LGA1151 !**
- **H310 Chipset !**
- **19" Enclosure !**

- Intel® 8th & 9th Core i3/i5/i7/Pentium Processor
- Support 2* DDR4 2666 SO-DIMM up to 32 GB
- 4* USB3.1, 2* USB2.0, 2* COM, 1* HDMI , 1* DP, 2* RJ45, Line-out/Line-in/MIC
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 250W FLEX Power

Dimensions	– 330 (W) x 192 (D) x 44 (H) mm	
MB model	– MI98-00 / Mini ITX (6.7-in * 6.7-in, 170 * 170mm)	
Part No	Non-Wifi	Wifi
	– HBJC150I98-H310-B	– HBJC150I98W-H310-B
CPU	– Intel® 8/9th Core i3/i5/i7/Pentium/Celeron LGA Processor (TDP: 95W)	
BIOS	– AMI Flash ROM	
Memory	– 2* Dual CH non-ECC DDR4 2666 MHz SDRAM SO-DIMM up to 32GB	
Network	– 2* GbE (1*Intel i219V, 1* Realtek 8111H)	

Storage	<ul style="list-style-type: none"> - 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay - 1 *M.2_SSD (M key-2242/2280) support NVMe
Expansion	<ul style="list-style-type: none"> - 1* M.2 E-key 2230 (PCIex1/USB2.0) - Support onboard TPM2.0 (MI98-02) / optional
Rear I/O Port	<ul style="list-style-type: none"> - 4 * USB 3.1 (Gen. 1) - 1 * HDMI (Max Resolution: 4096×2160@30Hz) - 1 * DP (Max Resolution: 4096×2304@60Hz) - 2 * RJ45 (1*Intel i219V, 1* Realtek 8111H) - 1 * Mic , 1 * Line in , 1 * Line-out - 2 * COM (COM 1 support RS232/422/485) - AC-in
Front I/O Port	<ul style="list-style-type: none"> - 1 * Power button - 1 * Reset button - 1 * Power LED - 1 * HDD LED - 2 * USB 2.0
Power Source	<ul style="list-style-type: none"> - 1U 250W FLEX POWER - AC 90~240V input
Certification	<ul style="list-style-type: none"> - CE, FCC, LVD, RoHS
Environment	<ul style="list-style-type: none"> - Operating Temperature : 0°C~50°C - Storage Temperature : -10°C~70°C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
Packing	<ul style="list-style-type: none"> - Net Weight : 3.5 KG - Gross Weight : 4.5 KG - Color Box Dimension : 560(W) x 400(D) x 140(H) mm