



819.00 EUR

incl. 19% VAT, plus shipping

- **BayTrail-D J1900 !**
- **4GB RAM !**
- **IP65 !**
- **9-28V DC !**

- 13.4" 220 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Intel® Bay Trail-D J1900 2.0GHz/QC processor
- Onboard DDR3L 1333MHz DRAM 4GB
- 2* GbE, 2* RS232/422/485), 2* RS232, 2* USB3.0, 2* USB2.0, 1* VGA
- 1* Mini PCIe, 1* M.2 M-key (2242/2260/2280, SATA interface)
- 9~28V DC-in
- Front bezel meets IP65-rated protection

Display	<ul style="list-style-type: none"> - IP65, NEMA 4 rugged protection, Full planar metal border - 13.4" With LED Backlight - 220 nits Brightness (cd/m²) - 262K display color - 1366 x 768 @ 60Hz resolution - 90°/65° viewing angle (H/V) - 0.17925 x 0.17925 mm pixel pitch - 16:9 aspect ratio - 500:1 contrast ratio - 11ms response time
Touch Screen	<ul style="list-style-type: none"> - Projected capacitive type - 340.00 x 200.00mm ±0.3mm active range - Transparency ≥ 85% - Surface Hardness ≥ 6H (JIS-5400) - Glass haze value ≤ 3%
Case	<ul style="list-style-type: none"> - Aluminum panel - Iron case - Silver + Black color - Spray paint coating requirement
Main System	<ul style="list-style-type: none"> - Intel® Bay Trail-D J1900 2.0GHz/QC processor - Onboard DDR3L 1333MHz DRAM 4GB - 64MB SPI Flash ROM BIOS - Watchdog Timer: 256 levels, 0~255 sec. - OS Support: Windows 7 / 8.1 / 10 / Linux (Option)
Expansion	<ul style="list-style-type: none"> - 1* Mini PCIe for WIFI or 3G/4G
Storage	<ul style="list-style-type: none"> - 1* SATA - 1* M.2 M-key (2242/2260/2280, SATA Interface)
I/O Connector	<ul style="list-style-type: none"> - 2* USB3.0 - 2* USB2.0 - 2* RS232/422/485 - 2* RS232 - 1* VGA - 2* RJ45 (Intel I211AT GbE) - 1* Lockable 9~28V DC jack - 1* Power button

Power Input	<ul style="list-style-type: none"> - 9~28V DC-in - AC version: 100~240V AC-DC 60W power adapter or - DC version: 12VDC with over current protection fuse
Power Consumption	<ul style="list-style-type: none"> - 20W
Dimensions	<ul style="list-style-type: none"> - 347.42 * 228.00 * 56.60mm
Compliance	<ul style="list-style-type: none"> - CE, FCC, IP65 (Front)
Safety	<ul style="list-style-type: none"> - Shock: 15G, 11ms duration - Vibration: 5~500Hz/1 Grms
Temperature	<ul style="list-style-type: none"> - Operating: : -10°C ~ 60°C (with W.T. DRAM/HDD in airflow condition) - Operating: : -10°C ~ 60°C (with W.T. DRAM/HDD) - Storage: -20°C ~ 85°C