



579.00 EUR

incl. 19% VAT, plus shipping

• **STC-48750**

Now you can power every PC in your truck. 750W power and P4 connector are giving you all possibilities !

The ATX connector has 24 pins.

Dimensions	170mm[W] × 150mm[L] × 86mm[H]
Weight	3.0 kgs
Input Voltage Range	37 - 71V VDC
Output Power maximum	750W
Efficiency	75% typical @48V DC Full Load
Output Power maximum (rails)	+3.3V : 35A +5.0V : 60A +12.0V : 48A
Over Power Protection	Peak power protected to 130%±10% of continuous rated power
Over Voltage Protection	+3.3V@4.5V, +5V@6V, +12V@15.6V
Short Circuit Protection	All output equipped with SCP (shutdown and latch off)

MTBF	100 000 hours @max. Load, 48V DC & 25°C ambient
Safety Standards	Meet IEC60950-1, EN60950-1
Operating Temperature	0°C ~ +50°C full load
Storage Temperature / Humidity	-20°C~+80°C / 10%~90% RH. (Non condensing)
Cooling	80x80x25 mm Fan x 1 pc, 70dBA @ Full Load
Connectors	1x ATX 24Pin 1x +12V(P4) 4pin 2x 4pin HDD/DVD 1x 4pin FDD 4x Serial ATA 4x 8pin Process EPS 3x PCIe (6+2)