

289.00 EUR

incl. 19% VAT, plus shipping

- **Intel Comet Lake !**
- **HBJC330U95V Series !!**



- Intel® 5205U SoC Processor
- Support Dual Channel DDR4 2666MHz up to 64GB
- 1* Intel® I219LM GbE, 1* Intel® I225-V 2.5GbE
- 1* M.2 (M-key, SATA interface), 1* M.2 (E-key, support CNVi)
- 1* RS232/RS422/485, 4* USB3.2
- 1* DP, 2* HDMI
- 12~24V DC-in

Model	<ul style="list-style-type: none"> - HBJC330U95V-10210 (CPU : 10210U, default) - HBJC330U95VI-10210 (CPU : 10210U, Wifi) - HBJC330U95V-5205 (CPU : 5205U) - HBJC330U95VI-5205 (CPU : 5205U, Wifi)
CPU/Chipset	<ul style="list-style-type: none"> - Intel® Comet Lake i5-10210U 1.6G QC SoC Processor - Intel® Comet Lake 5205U SoC Porcessor

BIOS	- AMI 128MB SMT Flash ROM
Memory	- 2 * DDR4 2666MHz SO-DIMM up to 64GB
Network	- 1* Intel® I219LM GbE - 1* Intel® I225-V 2.5GbE
Graphics	- 1* HDMI1.4 (Max Resolution : 4096×2304@30Hz) - 1* HDMI2.0 (Max Resolution : 4096×2304@60Hz) - 1* DP (Max Resolution : 4096×2304@60Hz) - Support Triple Displays
Storage	- 1 * M.2 (M-Key, 2242, SATA interface)
Expansion	- N/A
Rear Panel I/O	- 2 * USB3.2 (Gen2) - 1 * DP1.4 - 1 * HDMI2.0 - 1 * HDMI1.4 - 2 * RJ45 - 1 * DC Jack (12~24V)
Front Panel I/O	- 1 * Audio Jack (Line out +MIC) - 2 * USB3.2 (Gen2) - 1 * RS232/422/485 - 1 * Power Button
Internal Connector	- 1 * M.2 (M-Key, SATA Interface) - 1 * M.2 (E-Key) for CNVi or PCI-E/USB WIFI/BT - 8bit GPIO - 2 * USB2.0
Power Source	- 12~24V DC-in - Adapter: DC 19V/6.32A 120W
Compliance	- CE, FCC, RoHS, ErP Ready (Option)
Temperature	- Operating Temperature: -10 ~ 50° C - Storage Temperature: -20 ~ 60° C
Dimensions	- 150 (W) x 106 (D) x 75 (H) mm
OS Support	- Windows 10, Linux