



749.00 EUR

incl. 19% VAT, plus shipping

- **Intel 10/11th Gen. Socket !**
- **LGA1200 !**
- **HBFFI02 !**

- Intel LGA1200 Socket 10/11th generation Pentium, Core i3, i5, i7 Processors, up to 35W
- Dual CH non-ECC DDR4 2933/2666/2400MHz SODIMM
- 1\* 2.5" HDD TRAY Design
- Support 2\* HDMI, 1\* DP, 4\* COM, 2\* USB2.0, 4\* USB 3.2, 1\* Line-out, 1\* MIC
- Adapter DC19V 120W

MB Model	- MI02-Q470 Series/ Mini-ITX		
Part No	Non-Wifi	M.2 ac WiFi card	TPM2.0
	- HBFFI02-Q470-B	- HBFFI02I-Q470-B (WIFI)	- HBFFI02-Q470-T (non-WIFI + TPM2.0) - HBFFI02I-Q470-T (WIFI + TPM2.0)
BIOS	- AMI Flash ROM		
CPU/Chipset	- INTEL® LGA 1200 Socket 10/11th generation Core i7 / i5 / i3 / Pentium CPU (35W) - INTEL® Q470E chipset Notes : When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.		
Memory	- 2 * SO-DIMM slots / dual channel DDR4 2933/2666/2400MHz up to 64GB * Core i9 / i7 CPUs support DDR4 up to 2933MHz * Core i5 / i3 CPUs support DDR4 up to 2666MHz * Pentium / Celeron CPUs support DDR4 up to 2400MHz		

Network	<ul style="list-style-type: none"> <li>- 1 * Intel i219LM GbE</li> <li>- 1 * Intel i225LM 2.5GbE</li> </ul>
Storage	<ul style="list-style-type: none"> <li>- 1 * 2.5" SATAIII 6Gb/s internal drive bay (only support 2.5" HDD with a height ≤ 10mm)</li> <li>- 1 * M.2 M-Key 2280 (SATA/PCIex4) support NVMe</li> </ul>
Expansion slot	<ul style="list-style-type: none"> <li>- 1 * M.2 E-Key, 2230 (PCIe x1 /USB2.0) support CNVi</li> <li>- 1 * M.2 B-Key 3042/3052 (USB3.0/USB2.0/PCIe x1) W/SIM card holder</li> </ul>
Rear Panel I/O	<ul style="list-style-type: none"> <li>- 4 * USB 3.2</li> <li>- 2 * HDMI (Max Resolution: 4096×2160@30Hz)</li> <li>- 1 * DP (Max Resolution: 4096×2304@60Hz)</li> <li>- 2 * RJ45</li> <li>- 1 * Line-out, 1 * MIC</li> <li>- 4 * COM</li> <li>- 1 * DC-in</li> </ul>
Front Panel I/O	<ul style="list-style-type: none"> <li>- 1 * Power button, 1 * Power LED, 1 * HDD LED</li> <li>- 2 * USB 2.0</li> <li>- 1 * 2.5" HDD Tray (Easy to replace the hard disk, does not support hot swap)</li> </ul>
Compliance	<ul style="list-style-type: none"> <li>- CE, FCC, LVD, RoHS, ErP Ready</li> </ul>
Power Source	<ul style="list-style-type: none"> <li>- MB : DC12~28V input</li> <li>- Adapter : AC110~240V to DC19V-6.3A 120W</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>- Operating Temperature: -20 ~ 50° C (<a href="#">The test environment is closed and windless</a>)</li> <li>- Storage Temperature: -10 ~ 70° C</li> <li>- Humidity: 90% , non-condensing</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>- 290 (W) x 207 (D) x 65 (H) mm</li> </ul>
Packing	<ul style="list-style-type: none"> <li>- Net Weight: 3.8KG</li> <li>- Gross Weight: 4.8KG</li> <li>- Color Box dimension: 406 (W) * 148 (D) * 359 (H) mm</li> </ul>
OS Support	<ul style="list-style-type: none"> <li>- Windows 10, Linux</li> </ul>