



79.95 EUR

incl. 19% VAT, plus shipping

Special offer. Like PH12FEI-H310-19V, but only 1x LAN, without PCIe, without Serial/MAPI header.

- Intel® Coffee Lake Core i7/i5/i3 / Pentium / Celeron LGA1151 processors
- Intel H310 Chipset
- 2x DDR4 SO-DIMM, support up to 32GB
- Support triple display for HDMI, Display Port and LVDS
- 3x SATA III
- 1x Intel Gigabit Ethernet
- 6x USB 2.0, 4 x USB3.1 (Gen 2)
- DC-in 19V power input

Attention : M.2 slot is without function.

### **PH12FEI (PH12FEI) Specifications**

**MECHANICAL**

**FORM FACTOR**

Mini-ITX: 6.7" x 6.7"  
(170 mm x 170 mm)

## PH12FEI (PH12FEI) Specifications

### SYSTEM

PROCESSOR	9th & 8th Gen Intel Coffee Lake LGA1151 Socket Processor, Core i7/i5/i3 6-core TDP Max. 65W, Core i9 8-core TDP Max 35W
CHIPSET	Intel® H310 / Intel® Q370 (Support RAID 0 / 1 / 5)
SYSTEM MEMORY	DDR4 2666MHz / 2 x 260-pin SO-DIMM / Max. 32GB (Non-ECC)
GRAPHICS	Intel® HD Graphics
ETHERNET	Intel® Giga LAN
AUDIO	Realtek® ALC662
I/O CHIPSET	Nuvoton NCT6116D
TPM	Nuvoton NPCT750AAAYX TPM2.0 (Optional)

### EXPANSION SLOT

BIOS	256 Mbit SPI
H/W MONITOR	Temperature Monitor / Voltage Monitor / Fan Monitor
WATCHDOG TIMER	1~255 steps by software program
SMART FAN CONTROL	CPU Fan / System Fan

### GRAPHICS

VGA	-
DVI	-
HDMI	Up to 4K (4096 x 2160) @30 Hz
DISPLAYPORT	Up to 4K (4096 x 2304) @60 Hz
LVDS	Up to 1920 x 1200 @60 Hz
eDP (Option)	Up to 4K (4096 x 2304) @60 Hz

### REAR I/O

USB	4 x USB 3.1 Gen 2 / 4 x USB 3.0 (H310)
DISPLAY I/O	1 x HDMI 1.4 / 1 x DisplayPort 1.2
AUDIO I/O	1 x Mic-in / 1 x Line-out
LAN I/O	1 x RJ-45
SERIAL PORT	-
PS/2 PORT	-

## PH12FEI (PH12FEI) Specifications

	OTHERS	DC-in 19V (5.1 mm / ID, 7.4 mm / OD)
INTERNAL CONNECTORS	STORAGE	3 x SATAIII
	USB	6 x USB 2.0 (Q370) / 5 x USB 2.0 (H310)
	DISPLAY I/O	1 x LVDS (*Optional eDP SKU available) / 1 x Backlight Connector
	AUDIO I/O	1 x Audio Header (Front Panel Mic-in & Line-out)
	SERIAL PORT	-
	PARALLEL PORT	-
	GPIO	-
	FAN	1 x 4-pin CPU Fan Header / 1 x 4-pin System Fan Header
	POWER	1 x ATX Power Connector / 1 x AT / ATX Mode Select Jumper
	OTHERS	1 x Chassis Intrusion / 1 x CMOS Jumper
POWER REQUIREMENT	POWER INPUT	DC-in 19V (5.1 mm / ID, 7.4 mm / OD) / ATX 2-pin 19V
ENVIRONMENTAL	OPERATING TEMPERATURE	0 ~ 60°C (32 ~140°F)
	STORAGE TEMPERATURE	-20 ~ 80°C (-4 ~176°F)
	OPERATING HUMIDITY	10% ~ 95% R/H (Non-condensing)
	CERTIFICATION	CE / FCC Class B
OS	OS SUPPORT	Windows® 10 64-bit / Linux (support by request)
PACKING LIST	PACKAGE	1 x Motherboard / 1 x 50 cm SATA Cable / 1 x 45 cm SATA Power Cable / 2 x I/O Bracket (Half and Full Height) / 1 x Quick Installation Guide / 1 x ATX 4-pin to DIN 4-pin Cable (12v SKU only)