



269.00 EUR

incl. 19% VAT, plus shipping

- **J1900 BayTrail !**
- **1x COM !**
- **1x Parallel Port !**
- **MiniITX !**

- Intel® Bay Trail J1900 2.0GHz/QC Core MCP Processor (Turbo 2.42GHz)
- 1* DDR3L 1333MHz up to 8GB
- 2* Realtek® RTL8119I GbE
- 1* SATAII, 1*M.2 (M-key)
- 1* VGA, 1* HDMI, 1* LVDS
- 1* RS232/422/485, 5* RS232, 1*USB3.0, 7* USB2.0, 1* Parallel
- 1* Mini PCIe Support WIFI/BT/4G Module
- 1* M.2 M-key (2242/2280) support SSD
- 12V DC-in
- Mini ITX Form Factor (170 x 170 mm)

Model	– JLI1N-0L
Form Factor	– ITX (170 * 170mm)
Processor System	– Intel® Bay Trail J1900 2.0GHz/QC, 10W, Core MCP Processor (Turbo 2.42GHz) – AMI 32M Flash ROM BIOS

Memory	<ul style="list-style-type: none"> - 1* DDR3L 1333MHz SO-DIMM up to 8GB
Storage	<ul style="list-style-type: none"> - 1* SATAII (3.0Gb/s) - 1* M.2 M-key (2242/2280, SATA interface)
Expansion	<ul style="list-style-type: none"> - 1* Full size Mini PCIe - 1* PCIe x1 - 1* SIM card slot
Ethernet	<ul style="list-style-type: none"> - 2* Realtek RTL8119I GbE
Graphics	<ul style="list-style-type: none"> - Intel® Z3700 Graphics, shared memory - 1* HDMI 1.4 (Max Resolution: 2560×1600@60Hz) - 1* LVDS (Max Resolution: 2560×1600@60Hz) - 1* VGA (Max Resolution: 1920×1080@60Hz) - Support Dual Displays
Audio	<ul style="list-style-type: none"> - USB Audio, 3W Amplifier
Watchdog Timer	<ul style="list-style-type: none"> - From Super I/O to drag RESETCON# - 256 segments (10sec ~ 255min)
Internal I/O	<ul style="list-style-type: none"> - 4* USB2.0 - 1* RS232/422/485 - 4* RS232 - 1* SATAII - 1* SATA power - 1* M.2 (M-key, 2242/2280) - 1* Full size Mini PCIe - 1* GPIO (16bit, 5V, Co-lay Parallel) - 1* PCIe x1 - 1* SIM card slot - 1* AT mode - 1* Case Open - 1* FP_Audio Header - 2* 3W Amplifier - 1* CPU FAN

External I/O	<ul style="list-style-type: none">- 1* VGA- 2* RJ45- 1* USB3.0- 3* USB2.0- 1* RS232- 1* Parallel (Co-lay GPIO)- Line-out- 12V DC-in
Power	<p>DC-in 12V</p> <ul style="list-style-type: none">- AT: Directly PWR on as Power input ready- ATX: Press Button to PWR on after Power input ready
Compliance	<ul style="list-style-type: none">- CE, FCC, RoHS, REACH
Temperature	<ul style="list-style-type: none">- Operating: 0°C ~ 60°C- Storage: -20°C ~ 70°C- Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none">- Windows 7 / 8 /10, Linux