


298.00 EUR

incl. 19% VAT, plus shipping

- **N2930 BayTrail !**
- **5x COM !**
- **miniITX !**



- 1. Support Intel® Bay Trail N2930 SoC Processor
- 1* DDR3L 1333MHz SO-DIMM up to 8GB
- 1* 10/100/1000 Base-TX Ethernet Port
- 1* HDMI, 1* VGA, 1* LVDS (co-layout with eDP)
- 5* COM (COM1 support RS232/422/485), 1* USB3.0, 7* USB2.0
- 1* M.2 M-key 2242/2280 (SATA interface), 1* M.2 E-key 2230 (PCIe x1/USB2.0 interface), 1* M.2 B-key 3042 (USB2.0 interface) W/SIM card holder
- 1* SATA II (3Gb/s)
- Support 12V DC-in PWR
- 1* PCIe x1 slot

Model	<ul style="list-style-type: none"> – MI97R30 – MI97R32 (Equipped with TPM2.0 model)
Form Factor	– Mini ITX (170 * 170mm)

Processor System	<ul style="list-style-type: none"> – Intel® Bay Trail N2930 SoC Processor – AMI Flash ROM BIOS
Expansion Slot	<ul style="list-style-type: none"> – 1* M.2 (E-key, 2230. USB2.0 & PCIe1 interface) – 1* M.2 (B-key, 3042. USB2.0 interface) W/SIM card holder – 1* PCIe x1 slot
Memory	<ul style="list-style-type: none"> – 1* SO-DIMM DDR3L 1333MHz Single CH SDRAM up to 8GB
Graphics	<ul style="list-style-type: none"> – Intel® HD Graphics, shared memory – 1* LVDS (Max Resolution: 1920×1200@60Hz) – 1* eDP (Max Resolution: 2560×1600@60Hz), Co-layout with LVDS – 1* VGA (Max Resolution: 1920×1080@60Hz) – 1* HDMI (Max Resolution: 1920×1200@60Hz)
Ethernet	<ul style="list-style-type: none"> – 1* Realtek RTL8119I GbE
Audio	<ul style="list-style-type: none"> – 4 channel HD audio: Realtek® ALC888S
Storage	<ul style="list-style-type: none"> – 1* SATAII – 1* M.2 (M-key, 2242/2280. SATA interface)
Rear I/O	<ul style="list-style-type: none"> – 1* USB3.0 – 3* USB2.0 – 1* HDMI – 1* VGA – 1* PS/2 – 1* RJ45 – 2* COM (COM1 support RS232/422/485) – 1* Parallel – Line-out/MIC – 1* 12V DC-in PWR
Internal Connector	<ul style="list-style-type: none"> – 4* USB2.0 – 3* COM (RS232) – 1* LVDS (co-layout with eDP) – 1* SATAII – 1* SIM card holder – 1* GPIO (8 bit) – 1* Audio Header (W/3W Amp.) – 1* SMBUS – 1* CPU FAN – 1* TPM2.0 onboard (MI97R32)

Watchdog Timer	<ul style="list-style-type: none">– From Super I/O to drag RESETCON#– 256 segments (10sec ~ 255min)
Power	<p>12V DC-in (2-pin PWR Con)</p> <ul style="list-style-type: none">– AT: Directly PWR on as Power input ready– ATX: Press Button to PWR on after Power input ready
Compliance	<ul style="list-style-type: none">– CE, FCC, LVD, RoHS, REACH
Temperature	<ul style="list-style-type: none">– Operating: 0°C ~ 60°C(with 0.7m/s air flow)– Storage: -20°C ~ 85°C– Humidity: 10% ~ 90% RH @40°C (non-condensing)