



339.00 EUR

incl. 19% VAT, plus shipping

- **Intel Elkhart Lake SoC !**
- **2x LAN !**

- Intel Elkhart Lake SoC Processor
- 1* DDR4 3200MHz SO-DIMM up to 32GB
- 1* HDMI, 2* USB3.1, 1* USB-C, 2* RJ45, 1* COM
- Support 9~36V wide voltage input
- DC12V_40W Adapter

Model	- HBFBP01-6210-B - HBFBP01I-6210-B (WiFi model)
CPU/Chipset	- Intel® Elkhart Lake SoC Processor
BIOS	- AMI Flash ROM
Memory	- 1* DDR4 3200MHz Dual Channel SO-DIMM up to 32GB
Storage	- 1* M.2 M-key (2242, PCIe Gen.3 x2/SATA interface) support NVMe
Expansion	- 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface)

Rear Panel I/O	<ul style="list-style-type: none"> - 2* RJ45 - 1* DC-in - 1* HDMI - 2* USB3.1(Gen.2) A Type - 1* USB3.1(Gen.2) C Type
Front Panel I/O	<ul style="list-style-type: none"> - 1* Power button + Power LED - 1* RS232/422/485
Internal Connector	<ul style="list-style-type: none"> - 1* GPIO - 2* USB2.0
Power Source	<ul style="list-style-type: none"> - Adapter : AC 90~240V input / DC12V_40W output / Lock type - System : DC9~36V input support
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD, RoHS, ErP Ready
Dimensions	<ul style="list-style-type: none"> - System: 125 (W) x 109 (D) x 44.5 (H) mm - Color Box : 158 (W) x 167 (D) x 123.6 (H) mm
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -20 ~ 60° C (Under the condition of using M.2 interface SSD) - Storage Temperature: -40 ~ 85° C - Humidity: 10% ~ 95% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none"> - Windows 11, Linux