

649.00 EUR

incl. 19% VAT, plus shipping



- **LGA1700 !**
- **H610 Chipset !**
- **2x LAN !!**
- **2x COM !**

- Intel® 12/13th LGA1700 Socket Processor (Max. 65W TDPs)
- Intel® H610 Chipset
- 2* DDR5 4800MHz SO-DIMM up to 64GB
- 8* USB, 2* RJ45, 1* MIC, 1* Line-out, 1* Line-in, 2* COM, 1* DP, 1* HDMI, 1* VGA
- Onboard TPM2.0 (optional)

Model	- HBJC150I225-Q670B - HBJC150I225-H610B
MB Model	- MI225Q6700 - MI225H6100
CPU/Chipset	- Intel® 12th/13th LGA1700 Socket Core i7/i5/i3/Pentium/Celeron Processor (Max. 65W TDPs under 180A) - Intel® H610 Express Chipset
BIOS	- AMI Flash ROM
Memory	- 2* Dual CH non-ECC DDR5 4800MHz SDRAM SO-DIMM up to 64GB
Network	- HBJC150I225-Q670: 1* Intel® i219-LM GbE + 1* Intel® i225-V 2.5GbE - HBJC150I225-H610: 1* Intel® i219-V GbE + 1* Intel® i225-V 2.5GbE

Graphics	<ul style="list-style-type: none"> - Intel® UHD Graphics, shared memory - 1* DP 1.4a (Max Resolution: 4096×2304@60Hz) - 1* HDMI 2.0b (Max Resolution: 4096×2160@60Hz) - 1* VGA (Max Resolution: 1920×1080@60Hz)
Storage	<ul style="list-style-type: none"> - 2* SATAIII (6 Gb/s) 2.5" Device , support RAID 0, 1 - 1* M.2 M-Key (2280, PCIe Gen.3 x4 interface) support NVMe - 1* M.2 M-Key (2242, PCIe Gen.4 x4/SATA interface) support NVMe (HBJC150I225-Q670 only)
Expansion	<ul style="list-style-type: none"> - 1* M.2 E-Key (2230, USB2.0/PCIe Gen.3 x1 interface) support CNVi - 1* M.2 B-key (3042, PCIe Gen.3 x1/USB3.2 Gen.2/USB2.0 interface) (HBJC150I225-Q670 only) - 1* M.2 B-key (3042, PCIe Gen.3 x1 interface) (HBJC150I225-H610 only) - 1* PCIe Gen.4 x16
Rear Panel I/O	<ul style="list-style-type: none"> - 2* RJ45 - 6* USB3.2(Gen.2) (HBJC150I225-Q670) - 4* USB3.2(Gen.2) + 2* USB2.0 (HBJC150I225-H610) - 1* HDMI - 1* DP - 1* VGA - 2* COM - 1* Audio (Line-in, Line-out, MIC)
Front Panel I/O	<ul style="list-style-type: none"> - 1* Power button, 1* Reset button - 2* USB2.0 - 1* Power LED, 1* HDD LED
Internal Connector	<ul style="list-style-type: none"> - SIM Card slot - 1* GPIO (8 bit) - TPM2.0 (optional)
Power Source	<ul style="list-style-type: none"> - 1U FLEX 300W ATX PWR (4+24 pin)
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD, RoHS, ErP Ready
Dimensions	<ul style="list-style-type: none"> - Operating Temperature: 0 ~ 50° C - Storage Temperature: -40 ~ 85° C - Humidity: 10% ~ 95% RH @40°C (non-condensing)

Temperature

- Operating Temperature: 0 ~ 50° C
- Storage Temperature: -40 ~ 85° C
- Humidity: 10%~95% @40° C (non-condensing)

OS Support

- Windows 11, Linux