



639.00 EUR

incl. 19% VAT, plus shipping

- **LGA1200 !**
- **2x LAN !**
- **2x COM !**

- Intel® LGA1200 Socket support 10th/11th Gen Core™ Processor
- Support 2\* DDR4 3200/2933MHz SO-DIMM up to 64 GB
- 4\* USB3.2 (Gen2), 2\* USB3.2 (Gen1), 2\* USB2.0, 2\* COM, 1\* HDMI , 1\* DP, 1\* VGA, 2\* RJ45, 1\* MIC, 1\* Line out , Line in
- M/B Form Factor : Mini ITX (170x170mm)
- 1U FLEX 250W ATX Power
- Support TPM2.0 (option)

Model	- HBJC150LI22-H420B (non-Wifi) - HBJC150LI22I-H420B (M.2 ac Wifi)
CPU/Chipset	- Intel® 10th/11th LGA 1200 Socket Core i7/i5/i3/Pentium/ Celeron Processor(Max. 65W TDP)
BIOS	- AMI Flash ROM
Memory	- 2* DDR4 3200/2933MHz SDRAM SO-DIMM up to 64GB
Network	- 1* Intel i219-LM GbE - 1* Intel i226-V 2.5GbE

Graphics	<ul style="list-style-type: none"> <li>- Intel® HD Graphics, shared memory, Support Dual Displays</li> <li>- 1* VGA (Max Resolution: 1920×1080@60Hz)</li> <li>- 1* HDMI 1.4 (Max Resolution: 4096×2160@30Hz)</li> <li>- 1* DP1.4 (Max Resolution: 5120×3200@60Hz)</li> <li>- Support Dual Display</li> </ul>
Storage	<ul style="list-style-type: none"> <li>- 2* 2.5" SATA Device</li> <li>- 1* M.2 M-key (2242/2280, PCIe x4 interface) support NVMe SSD</li> </ul>
Expansion	<ul style="list-style-type: none"> <li>- 1* M.2 E-key (2230, PCIe x1/USB2.0 interface) support CNVi for Wifi/BT</li> <li>- 1* PCIe x16 slot</li> </ul>
Rear Panel I/O	<ul style="list-style-type: none"> <li>- 2* RJ45</li> <li>- 1* DP</li> <li>- 1* HDMI</li> <li>- 1* VGA</li> <li>- 2* COM (RS232/422/485)</li> <li>- 4* USB3.2 (Gen.2)</li> <li>- 2* USB3.2 (Gen.1)</li> <li>- 1* Line-in, 1* Line-out, 1* MIC</li> </ul>
Front Panel I/O	<ul style="list-style-type: none"> <li>- 1* Power button, 1* Reset button</li> <li>- 1* Power LED, 1* HDD LED</li> <li>- 2* USB2.0</li> </ul>
Internal Connector	<ul style="list-style-type: none"> <li>- N.A</li> </ul>
Power Source	<ul style="list-style-type: none"> <li>- 1U FLEX 250W ATX POWER</li> <li>- AC 90~240V input</li> </ul>
Compliance	<ul style="list-style-type: none"> <li>- CE, FCC, RoHS, ErP Ready</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>- System: 430 (W) x 252 (D) x 44 (H) mm</li> <li>- Color Box dimension: 560 (W) x 400 (D) x 380 (H) mm</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>- Operating Temperature: 0 ~ 50° C</li> <li>- Storage Temperature: -10 ~70° C</li> <li>- Humidity: 10% ~ 90% RH @40°C (non-condensing)</li> </ul>
OS Support	<ul style="list-style-type: none"> <li>- Windows 11, Linux</li> </ul>