



869.00 EUR

incl. 19% VAT, plus shipping

- **LGA1700 !**
- **8x LAN !**
- **2x COM !**

- Intel® LGA1700 supports 12th Gen. Core Processor
- 2* DDR5 4800MHz SO-DIMM up to 64GB
- 2* 2.5" SATA HDD device support RAID 0, 1, 5, 10
- 1* M.2 (M-key, 2242/2280), 1* M.2 (M-key, 2280), 1* M.2 (E-key), 1* M.2 (B-key), 1* PCIe4
- 8* 2.5GbE, 2* USB3.2 (Gen.2), 2* USB3.2 (Gen.1), 2* COM
- 1* HDMI
- ATX Power Input with 24pin ATX + 4pin 12V
- Support TPM2.0 (option)

Model	- HBJC153I23-Q670B (Default) - HBJC153I23-Q670G4 (Expansion PCIe 4* Lan Card) system total up to 12* LAN ports - HBJC153I23-Q670B4 (Expansion PCIe 4* Bypass Lan Card) system total up to 12* LAN ports
MB Model	- MI23-Q6700 (Q670E) - MI23-Q6702 (optional , Q670E,onboard TPM2.0)
CPU/Chipset	- Intel® 12th/13th LGA1700 Socket Core i7/i5/i3/Pentium/Celeron Processor(Max. 65W TDPs under 180A) - Intel® Q670E Chipset

BIOS	<ul style="list-style-type: none"> - AMI Flash ROM - Support recover crashed BIOS data tool by a USB flash pen driver: Using JetBIOS SW back up tool with any external USB ports
Memory	<ul style="list-style-type: none"> - 2* DDR5 4800MHz SO-DIMM up to 64GB
Network	<ul style="list-style-type: none"> - 7* Intel® i225-V 2.5GbE - 1* Intel® i225-LM 2.5GbE
Graphics	<ul style="list-style-type: none"> - Intel® UHD Graphics, shared memory - 1* HDMI (Max Resolution: 1920×1080@60Hz)
Storage	<ul style="list-style-type: none"> - 1* M.2 M-key (2242/2280, PCIe Gen.4×4 w/SATA interface) - 1* M.2 M-key (2280, PCIe Gen.4×4 w/SATA interface) support NVMe - 2* 2.5" SATA HDD device support RAID 0, 1 (support 2.5" HDD with a height≤10mm)
Expansion	<ul style="list-style-type: none"> - 1* M.2 E-key (2230, USB2.0/PCIe x1) support CNVi - 1* M.2 B-key (3042, USB3.2 Gen.1/USB2.0/PCIe x1 interface) support 4G Module - 1* PCIe Gen.4×4 slot
Rear Panel I/O	<ul style="list-style-type: none"> - AC input CON - Power on/off SW
Front Panel I/O	<ul style="list-style-type: none"> - 8* RJ45 - 2* USB3.2 (Gen.2) - 2* USB3.2 (Gen.1) - 1* COM (RS232) (Not installed when leaving the factory, the wires are placed in the parts box) - 1* HDMI (Not installed when leaving the factory, the wires are placed in the parts box) - 1* Alarm LED, 1* Power LED - Power on/off SW
Internal Connector	<ul style="list-style-type: none"> - SIM Card Holder
Power Source	<ul style="list-style-type: none"> - Power : 1U FLEX 300W POWER - MB : ATX Power Input (24pin ATX + 4pin 12V)

Compliance	- CE, FCC, LVD, RoHS, ErP Ready
Dimensions	- System: 430 (W) x 252 (D) x 44(H) mm - Box: 560 (W) x 400 (D) x 380 (H) mm
Temperature	- Operating Temperature: 0 ~ 50° C - Storage Temperature: -40 ~ 85° C - Humidity: 10%~95% @40° C (non-condensing)
OS Support	- Windows 11, Linux