



798.00 EUR

incl. 19% VAT, plus shipping

- **AMD RYZEN V1605B !**
- **4x DP !**
- **6x USB !**
- **2x LAN !**

- AMD RYZEN V1605B 2.0GHz/QC Core Processor
- 2* DDR4 2400MHz up to 32GB
- 1* 2.5" SATA, 1* M.2 E-key, 1* M.2 M-key, 1* M.2 B-key
- Support 4* DP
- 2* COM (Max : 6* COM), 2* LAN, 2* USB3.2, 4* USB2.0, 1* Line in, 1* Line out, 1* Mic
- Mini ITX Form Factor (170 *170 mm)
- Support TPM2.0 (optional)
- DC12~28V input

Model	- HBJC501I1U-V1605B (non-WiFi) - HBJC501I1UI-V1605B (WiFi)
CPU/Chipset	- AMD (RYZEN) Core V1000 Series Processor (V1605B, TDP 15W)
BIOS	- AMI Flash ROM
Memory	- 2* DDR4 2400MHz SO-DIMM up to 32GB
Network	- 2* Realtek RTL8111H GbE
Graphics	- AMD Vega Core Architecture, shared memory - 4* DP1.4 (Max Resolution: 4096x2160@60Hz or 3840x2160@120Hz)

Storage	<ul style="list-style-type: none"> - 1* 2.5" SATA Device - 1* M.2 M-key (2242/2280, PCIe x2 interface)
Expansion	<ul style="list-style-type: none"> - 1* M.2 E-key (2230) support WiFi/BT module - 1* M.2 B-key (3042/3052) support 4G/5G module
Rear Panel I/O	<ul style="list-style-type: none"> - 2* RJ45 - 4* DP - 1* DC-in (Lockable) - 2* USB3.2 (Gen.1) - 2* USB2.0 - 2* COM (RS232/422/485) - 1* Line-in, 1* Line-out, 1* MIC
Front Panel I/O	<ul style="list-style-type: none"> - 1* Power button + Power LED - 1* HDD LED - 2* USB2.0 - 4* COM (RS232, optional)
Internal Connector	<ul style="list-style-type: none"> - SIM Card Holder (NANO type)
Power Source	<ul style="list-style-type: none"> - Adapter : AC 90~240V input / DC19V_90W output - MB : DC12~28V input
Compliance	<ul style="list-style-type: none"> - CE, FCC, RoHS, ErP Ready
Dimensions	<ul style="list-style-type: none"> - System: 264 (W) x 199.4 (D) x 58 (H) mm
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -20 ~ 60° C (Under the condition of using M.2 interface SSD) - Operating Temperature: 0 ~ 60° C (Under the condition of using 2.5" SATA HDD) (The test environment is closed and windless) - Storage Temperature: -20 ~ 60° C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none"> - Windows 11, Linux