



249.00 EUR

incl. 19% VAT, plus shipping

- **Intel Alder Lake-S H610 !**
- **Half High !**
- **Mini ITX !**

- Intel® 12/13th LGA1700 Socket Processor (Max. 65W TDP)
- Intel® Alder Lake-S H610 Chipset
- 2* DDR4 3200MHz UDIMM up to 64GB
- 1* HDMI, 1* DP, 1* LVDS or eDP
- 1* GbE
- 2* USB3.2 (Gen.2), 2* USB3.2(Gen.1), 5* USB2.0
- 1* M.2 M-key, 2242/2280(PCI-Ex4), 1* M.2 E-key, 2230, 2* SATAIII (6Gb/s)
- Onboard TPM2.0 (Option)
- 19V DC-in

Model	- LI25-H6100 - LI25-H6102 (TPM2.0)
Form Factor	- Mini-ITX (170 * 170mm)

Processor System	<ul style="list-style-type: none"> - Intel® 12/13th LGA1700 Socket Core i9/i7/i5/i3/Pentium/Celeron Processor (Max. 65W TDP) - Intel® Alder lake-S H610 chipset - AMI Flash ROM BIOS
Memory	<ul style="list-style-type: none"> - 2* DDR4 3200MHz Dual Channel SO-DIMM up to 64GB
Storage	<ul style="list-style-type: none"> - 2* SATAIII (6Gb/s) - 1* M.2 M-key (2242/2280 PCI-Ex4 Gen.3 interface)
Expansion	<ul style="list-style-type: none"> - 1* M.2 E-key (2230, CNVi/PCI-Ex1/USB2.0, Support WIFI/BT Module)
Ethernet	<ul style="list-style-type: none"> - 1* REALTEK® RTL8111H 10/100/1000Mbps
Graphics	<ul style="list-style-type: none"> - Intel® HD Graphics, shared memory - 1* EXT HDMI2.0 (Max Resolution: 4096×2160@60Hz) - 1* EXT DP1.4 (Max Resolution: 7680×4320@60Hz) - 1* INT LVDS (Max Resolution: 2560*1600@60Hz) - 1* INT EDP1.2 (Max Resolution: 1920*1080@60Hz) - Support Triple Displays
Audio	<ul style="list-style-type: none"> - HD audio: Realtek ALC897
Watchdog Timer	<ul style="list-style-type: none"> - From Super I/O to drag RESETCON# - 256 segments (10sec ~ 255min)
Internal I/O	<ul style="list-style-type: none"> - 2* USB3.2 (Gen.1) - 3* USB2.0 (PH2.54) - 1* 8bit GPIO (5V) - 2* SATAIII (6Gb/s) - 1* SATA Power - 1* LVDS(or eDP) + 1* Inverter - 1* 2pin Power connector - 1* Chassis intrusion - 1* FP_Audio - 1* 4pin Speaker header (for 3W Amplifier, PH2.0) - 1* 4pin Speaker header (for Buzzer, PH2.54) - 1* FP_JW - 1* SMBUS + 1*AT model - 1* CPU FAN Header (Smart FAN) + 1* SYSTEM FAN Header (W/O Smart FAN)

External I/O	<ul style="list-style-type: none">- 2* USB3.2 (Gen.2)- 2* USB2.0- 1* HDMI2.0- 1* DP1.4- 1* RJ45- 1* Line-Out- 1* MIC- 1* DC Jack (19V DC in)
Power	<p>19V DC in, AT/ATX Supported</p> <ul style="list-style-type: none">- AT: Directly PWR on as Power input ready- ATX: Press Button to PWR on after Power input ready
Compliance	<ul style="list-style-type: none">- CE, FCC, LVD, RoHS, REACH (Option)
Temperature	<ul style="list-style-type: none">- Operating Temperature: 0 ~ 60° C (with 0.7m/s air flow)- Storage Temperature: -20 ~ 70° C- Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none">- Windows 10 / 11, Linux