



989.00 EUR

incl. 19% VAT, plus shipping

- **Intel Elkhart Lake SoC !**
- **2x LAN !**
- **6x USB !**
- **HAILO-8 Card !**

- Intel Elkhart Lake SoC Processor
- 1* DDR4 3200MHz SO-DIMM up to 32GB
- 6* USB, 2* RJ45, 1* Audio (MIC + Line-out), 1* Line-IN, 3* DP, 2*COM, 1* GPIO
- Support TPM2.0
- 160.2*106*43.5 mm
- Hailo-8 M.2 M key module inside, up to 26 TOPS
- DC12V_60W Adapter

Model	- HB368F21-6412-AI (EMMC,TPM)
CPU/Chipset	- Intel® Elkhart Lake SoC Processor (J6412 , TDP 10W)
BIOS	- AMI Flash ROM
Memory	- 1* DDR4 3200MHz SO-DIMM up to 32GB
Network	- 2* Realtek RTL8119I GbE
Graphics	- Intel® HD Graphics, shared memory - 3* DP (Max Resolution: 4096×2160@60Hz) , Support Triple Displays
Storage	- 64GB eMMC onboard

Expansion	<ul style="list-style-type: none"> - 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface) - 1* M.2 B-key (3042,USB3.0 interface)
AI Accelerator	<ul style="list-style-type: none"> - 1* Hailo-8 M.2 M KEY module inside - 26 TOPS
Rear Panel I/O	<ul style="list-style-type: none"> - 2* RJ45 - 2* USB3.1(Gen.2) - 1* USB2.0 - 1* 8 bit GPIO (Phoenix Connector 2*9 PIN) - 2* RS232/422/485 (Phoenix Connector 2*9 PIN) - 1* DC in (Lockable)
Front Panel I/O	<ul style="list-style-type: none"> - 1* Power button + Power LED - 4* USB2.0 - 1* Audio(Line out+MIC) - 1* Line in - 3* DP
Internal Connector	<ul style="list-style-type: none"> - SIM Card Holder
Power Source	<ul style="list-style-type: none"> - Adapter : AC 90~240V input / DC12V_60W output - MB : DC12~36V input
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD, RoHS, ErP
Dimensions	<ul style="list-style-type: none"> - System: 160.2 (W) x 106 (D) x 43.5 (H) mm - Box: 250 (W) x 118 (D) x 295 (H) mm - Net Weight: 1.01KG - Gross Weight: 1.52KG
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -20 ~ 70° C - Storage Temperature: -40 ~ 85° C - Humidity: 10% ~ 95% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none"> - Windows 11, Linux