



329.00 EUR

incl. 19% VAT, plus shipping

- **LTE-M communication !**
- **Kineis satellite connectivity !**
- **Motion-Sensor !**

KT-520M is a GPS tracker with both LTE-M and Kineis satellite connectivity. This device will be used to locate vehicles/assets travelling between different locations, and transmit the location information via LTE-M, or Kineis satellite when there is no LTE-M coverage.

- LTE-M communication
- Kineis satellite connectivity
- Built-in GNSS solution
- Built-in 3-axis accelerometer for motion detection capability
- The device is powered by a SAFT D size 17Ah non-rechargeable battery
- Expected battery life of 5 years based 12 messages via LTE-M or 20 messages via Kineis per day
- The device shall operate in ambient temperature between -20°C and +55°C.
- Maintenance-free design.
- Configurable periodic report.
- The device shall measure or estimate the remaining battery level.
- It is possible to update the device firmware via LTE-M.
- Weight : approx. 280g
- Dimensions : 84.5 x 130.8 x 44 mm
- Ingress Protection : IP69K

LTE-M Connectivity	SIMCom LTE-M module
Kineis Connectivity	Kineis KIM1 module
LTE-M Antenna	Internal Antenna
Kineis Antenna	Internal Antenna (400MHz)
Transmission Frequency	Kineis @ 401MHz center frequency
Bandwidth	4 MHz
Output Power	1000mW
BLE	Built-in BLE chipset
GNSS	High sensitivity GNSS solution
G-Sensor	3-axis accelerometer
Battery	SAFT LS-33600 D size 17Ah non-rechargeable battery
Operation Temperature	-20°C ~ +55°C
Button	1 Button
LED	1 RGB LED
Weight	Estimated Weight 270g
Dimensions	W 84.5 x L 130.8 x D 44.0 mm
Ingress Protection	IP69K

Impact Protection	IK10
Certification	<ul style="list-style-type: none"><li>✦ FCC (TBC)</li><li>✦ CE, EMC, Safety (TBC)</li><li>✦ WEEE/RoHS (TBC)</li><li>✦ IP69K/IK10 (TBC)</li></ul>