



279.00 EUR

incl. 19% VAT, plus shipping

- **Intel Alder Lake-S !**
- **2* GbE LAN !**
- **10* USB !**
- **MiniITX !**

- Intel® 14/13/12th LGA1700 Socket Processor (Max.65W TDP)
- Intel® Alder Lake-S H610 chipset
- 2* DDR5 5600MHz/4800MHz UDIMM up to 64GB
- 2* HDMI, 1* VGA
- 2* REALTEK® RTL8111H GbE
- 4* USB3.2 (Gen.1), 8* USB2.0, 10* COM(RS232, COM1/2 Co-lay 422/485)
- 1* M.2 M-key 2242/2280(PCI-Ex4), 1* M.2 E-key 2230, 2* SATAIII
- Onboard TPM2.0(Optional)
- ATX Power

Model	- LI32-H6100 - LI32-H6102 (TPM2.0)
Form Factor	- Mini-ITX (170 * 170mm)

Processor System	<ul style="list-style-type: none"> - Intel® 14th/13th/12th LGA1700 Socket Core i9/i7/i5/i3/Pentium/Celeron Processor (Max. 65W TDP) - Intel® Alder lake-S H610 chipset - AMI Flash ROM BIOS
Memory	<ul style="list-style-type: none"> - Intel® 14/13th CPU support 2* DDR5 5600MHz Dual Channel DIMM up to 64GB - Intel® 12th CPU support 2* DDR5 4800MHz Dual Channel DIMM up to 64GB
Storage	<ul style="list-style-type: none"> - 2* SATAIII (6Gb/s) - 1* M.2 M-key (2242/2280 PCI-Ex4 Gen.3 interface)
Expansion	<ul style="list-style-type: none"> - 1* M.2 E-key (2230, CNVi/PCI-Ex1/USB2.0, Support WIFI/BT Module) - 1* PCI-Ex16 Slot
Ethernet	<ul style="list-style-type: none"> - 2* Realtek® RTL8111H 10/100/1000Mbps
Graphics	<ul style="list-style-type: none"> - Intel® HD Graphics, shared memory - 2* HDMI2.0 (Max Resolution: 4096×2160@60Hz) - 1* VGA (Max Resolution: 1920×1080@60Hz) - Support Triple Displays
Audio	<ul style="list-style-type: none"> - HD audio: Realtek ALC897
Watchdog Timer	<ul style="list-style-type: none"> - From Super I/O to drag RESETCON# - 256 segments (10sec ~ 255min)
Internal I/O	<ul style="list-style-type: none"> - 2* USB2.0 (PH2.54) - 8bit GPIO (5V) - 10* COM (RS232, COM1/2 Co-lay RS232/422/485) - 2* SATAIII (6Gb/s) - 1* Chassis intrusion - 1* FP_Audio - 1* FP_JW - 1* SMBUS - 1* AT model - 1* CPU FAN Header (Smart FAN) - 1* SYSTEM FAN Header (W/O Smart FAN)

External I/O	<ul style="list-style-type: none">- 4* USB3.2 (Gen.1)- 6* USB2.0- 1* PS/2- 2* HDMI2.0- 1* VGA- 2* RJ45- 1* Line-Out- 1* MIC- 1* 2pin Front Power connector
Power	<p>ATX PWR (4+24 Pin)</p> <ul style="list-style-type: none">- AT: Directly PWR on as Power input ready- ATX: Press Button to PWR on after Power input ready
Compliance	<ul style="list-style-type: none">- CE, FCC, LVD, RoHS, REACH (Option)
Temperature	<ul style="list-style-type: none">- Operating Temperature: 0 ~ 60° C- Storage Temperature: -20 ~ 70° C- Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none">- Windows 10 / 11, Linux