

2949.00 EUR

incl. 19% VAT, plus shipping



- **NVidia Jetson AGX !**
- **32 GB !**

- 120-pin high speed connector for MIPI SerDes cameras, such as GMSL2/FPD-linkIII/V-by-One® HS, to deploy in AMRs application
- 1x GbE & 1x 10G RJ-45 ethernet for dozens of IPcameras streaming simultaneously in smart security application
- 10GigE Vision camera connector for smart inspection
- 1xPCIe slot for multi-function expansion.
- 1xM.2.Ekey for Wi-Fi6E, 1xmPCIe for 4G & 5G with adaptercard, and 1xM.2 Mkey for SSD and capture
- Operating temperature: -25°C ~ 70°C
- Dimension: 141.5mm(W) x 133.5mm(L) x 63mm(H)

NVIDIA Jetson SoM	NVIDIA® Jetson AGX Orin™ module (32GB)
Networking	1x GbE RJ-45 1x 10G RJ-45 1x M.2 E key (for Wi-Fi 6E)
Display Output	1x HDMI 2.0 (3840x2160at 60Hz)
Temperature	Operating temperature -25°C~70°C Storage temperature -40°C ~ 85°C Relative humidity 40 °C @ 95%, Non-Condensing

MIPI & SerDes Camera (120-pin)	GMSL2/FPD-link III/V-by-One® HS(optional)
USB	1x USB 2.0 Micro-B for recovery 2x USB 2.0 Type-A 2x USB 3.2 Type-A
Audio	Intel HD Audio analog connector
Storage	1x micro-SD card slot
Expansion Header	<ul style="list-style-type: none"> • 40-pin (UART, SPI, CAN, I2C, I2S, GPIOs) • 1x M.2 E key (for Wi-Fi 6E) • 1x M.2M key (for SSD or AVerMedia capture card: CL312H1, CN311-H, CN312SW, CN312MW) • 1x Micro SIM socket • 1x mPCIe(for 4GLTE module or 5G module via adapter card) • 1x PCIe x16 • 1x CAN bus with transceiver • 120-pin (for MIPI SerDes)
Input Power	DC in jack on board & ATX 4-pin (54V/2.78A, 9V~54V is recommended)
Power Cord	US/JP/EU/UK/TW/AU/CN
Thermal Solution	Fan(optional)
Buttons	Power and Recovery
RTC Battery	Support RTC Battery and Battery Life Monitoring by MCU
Dimensions	141.5mm (W) x 133.5mm (L) x 63mm (H)
Certifications	CE, FCC, KC