



589.00 EUR

incl. 19% VAT, plus shipping

- **Intel i5-1135G7 SoC !**
- **MiniITX Thin !**
- **8x COM !**

- Intel® 11th Tiger Lake-UP3 SoC Processor (Default: 6305E 1.8GHz/DC)
- 1* DDR4 3200MHz SO-DIMM up to 32GB
- 1* HDMI, 1* LVDS/eDP, 1* eDP
- 2* Realtek® RTL8111H GbE
- 4* USB3.2 (Gen.1), 5* USB2.0, 9* COM (COM4/5 Support RS232/422/485)
- 1* M.2 M-key (2242/2280, PCIe x4), 1* M.2 E-key (2230), 1* SATAIII
- Onboard TPM2.0 (Option)
- 12-24V DC-in

Model	<p>– LI35-1135G7L</p> <p>More Options:</p> <ul style="list-style-type: none"> – LI35-6305EL (Default) – LI35-6305E2L (TPM2.0) – LI35-1115G4EL – LI35-1115G4E2L (TPM2.0) – LI35-1135G7L – LI35-1135G72L (TPM2.0) – LI35-1145G72L (TPM2.0)
-------	---

Form Factor	- Mini-ITX (170 * 170mm)
Processor System	- Intel® 11th Tiger Lake-UP3 6305E / 1115G4E / 1135G7 / 1145G7E SoC Processor - AMI Flash ROM BIOS
Memory	- 1* DDR4 3200MHz So-DIMM up to 32GB
Storage	- 1* SATAIII (6Gb/s) - 1* M.2 M-key (2242/2280 PCI-Ex4 Gen.3 interface, Support SSD)
Expansion	- 1* M.2 E-key (2230, CNVi/PCI-Ex1/USB2.0, Support WIFI/BT Module)
Ethernet	- 2* Realtek® RTL8111H 10/100/1000Mbps
Graphics	- Intel® HD Graphics, shared memory - 1* HDMI2.0 (Max Resolution: 4096×2160@60Hz) - 1* LVDS/EDP (Max Resolution: 1920×1200@60Hz) - 1* EDP (Max Resolution: 4096*2304@30Hz) - Support Triple Displays
Audio	- HD audio: Realtek ALC897 - Build-in Amplifier to support 3W Speaker
Watchdog Timer	- From Super I/O to drag RESETCON# - 256 segments (10sec ~ 255min)
Internal I/O	- 4* USB2.0 (PH2.54) - 1* USB2.0 (PH2.0) - 16bit GPIO (5V, Co-lay LPT) - 1* LPT (Co-lay GPIO) - 9* COM (COM4/5 Support RS232/422/485) - 1* SATAIII (6Gb/s) - 1* SATA Power - 1* Chassis intrusion - 1* FP_Audio - 1* Audio amplifier header to support left and right side Speakers - 1* FP_JW - 1* SMBUS - 1* AT model - 1* CPU FAN Header (Smart FAN) - 1* SYSTEM FAN (W/O Smart FAN)

External I/O	<ul style="list-style-type: none">- 4* USB3.2 (Gen.1)- 1* HDMI2.0- 2* RJ45- 1* COM (RS232)- 1* Line-Out- 1* MIC- 1* DC Jack (12-24V DC in)
Power	<p>12-24V DC-in, AT/ATX Supported</p> <ul style="list-style-type: none">- AT: Directly PWR on as Power input ready- ATX: Press Button to PWR on after Power input ready
Compliance	<ul style="list-style-type: none">- CE, FCC, LVD, RoHS, REACH (Option)
Temperature	<ul style="list-style-type: none">- Operating Temperature: 0 ~ 60° C- Storage Temperature: -20 ~ 70° C- Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none">- Windows 10 / 11, Linux