



519.00 EUR

incl. 19% VAT, plus shipping

- **Intel J6412 2.0GHz/QC !**
- **4x COM !**
- **Fanless !**
- **2x LAN !**

- Intel® Elkhart Lake J6412 2,0 GHz/QC Core MCP-Prozessor (Turbo 2,6 GHz)
- Unterstützt DDR4 3200/2933 bis zu 32 GB
- 2* Intel® I225-V 2,5 GbE
- 1* SATA III (6 Gb/s), 1* M.2 M-Schlüssel (NVMe/SATA)
- 1* M.2 E-Schlüssel (unterstützt WIFI/BT-Modul)
- 1* M.2 B-Schlüssel (unterstützt 4G/5G-Modul)
- 1* VGA, 1* HDMI
- 2* USB3.1 (Gen.1), 4* USB2.0, 2* RS485, 2* RS232
- Lüfterloses Kühl-Design
- 12 V DC-Eingang

Model	- HBJC903I1BV-6412L (MB: JLI1BV-0L, Mini-ITX)
CPU/Chipset	- Intel® Elkhart Lake J6412 2.0G/QC SoC processor (Turbo 2.6GHz)
BIOS	- AMI 128MB SMT Flash ROM
Memory	- 1* SO-DDR4 3200/2933MHz up to 32GB
Network	- 2* Intel® i225-V 2.5GbE

Graphics	<ul style="list-style-type: none"> - Intel® HD Graphics, shared memory - 1* VGA (Max Resolution : 1920×1080@60Hz) - 1* HDMI1.4 (Max Resolution : 4096×2340@30Hz)
Storage	<ul style="list-style-type: none"> - 1* 2.5" SATA 6Gb/s internal drive bay - 1* M.2 M key (2242/2280, SATA or NVMe)
Expansion	<ul style="list-style-type: none"> - 1* M.2 E key (2230) support WIFI/BT - 1* M.2 B key (3042/3052) support 4/5G Module
Rear Panel I/O	<ul style="list-style-type: none"> - 2* USB3.1 (Gen.1) - 2* USB2.0 - 1* VGA - 1* HDMI - 2* RS485 - 2* RS232 - 2* RJ45 - 1* Line-out - 1* MIC - 1* DC Jack - 2* Antenna - 1* GND Hold - 1* Power Button
Side Panel I/O	<ul style="list-style-type: none"> - 2* USB2.0
Internal Connector	<ul style="list-style-type: none"> - 1* Nano SIM Card slot
Power Source	<ul style="list-style-type: none"> - 12V DC-in - Adapter : DC_12V_5A / 60W
Compliance	<ul style="list-style-type: none"> - CE, FCC, RoHS, ErP Ready, Option
Dimensions	<ul style="list-style-type: none"> - System: 200.0 (W) x 180.4 (D) x 59.5 (H) mm - Net Weight: 2.27KG ; Gross Weight: 3.27KG
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -10 ~ 50° C - Storage Temperature: -20 ~ 60° C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none"> - Windows 10/11, Linux