



CARTFT.COM  
Shop for mobile  
PC- and GPS-Solutions

Jetway HPC156C-DCP1135G7 Panel-PC (15.6" TFT, Touch Panel, Intel i5-1135G7,  
12-36V DC) [FANLESS]

[<http://www.cartft.com/catalog/il/3679>]



1498.00 EUR

incl. 19% VAT, plus shipping

- Intel i5-1135G7 !
- 15.6" TFT !!
- Fanless !

- 15.6" 250 nits TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Support Open frameless design
- A true Flat, easy to clean front surface with edge to edge design
- Aluminum Die-Cast Panel PC series, support for easy HDD and DRAM installation
- Support Cable less design
- 12~36 V DC input Support, with Electrical Over Stress (EOS), OVP design
- VESA Support 100x100mm

Display	<ul style="list-style-type: none"> <li>- NEMA 4 rugged protection, metal front bezel</li> <li>- 15.6" With LED Backlight</li> <li>- 250 nits</li> <li>- 262K display color</li> <li>- 1920 x 1080 @60Hz resolution</li> <li>- 170°/170° viewing angle (H/V)</li> <li>- 0.17925 x 0.17925mm pixel pitch</li> <li>- 16:9 aspect ratio</li> <li>- 800:1 contrast ratio</li> <li>- 35ms response time</li> </ul>
Touch Screen	<ul style="list-style-type: none"> <li>- projected capacitive type</li> <li>- 386.81 x 237.12mm ±0.3mm active range</li> <li>- Transparency ≥ 85%</li> <li>- Surface Hardness ≥ 6H (JIS-5400)</li> </ul>
Case	<ul style="list-style-type: none"> <li>- Aluminum panel</li> <li>- Iron case</li> <li>- White color</li> <li>- Spray paint coating requirement</li> </ul>
Main System	<ul style="list-style-type: none"> <li>- Intel® Tiger Lake i5-1135G7 2.4GHz/QC processor</li> <li>- 2* DDR4 SO-DIMM (Max 64GB)</li> <li>- 256MB SPI Flash ROM</li> <li>- Watchdog Timer 256 levels, 0~255 sec.</li> <li>- OS Support Windows 10 / Linux</li> </ul>
Expansion	<ul style="list-style-type: none"> <li>- 1* M.2 E key (2230) for WIFI</li> <li>- 1* M.2 B key (3042/3052/6570) for 4G/5G Module (4pcs Built in Antenna)</li> </ul>
Storage	<ul style="list-style-type: none"> <li>- 1* 2.5" SATA HDD</li> <li>- 1* M.2 M key (2242/2280, PCI-Ex4)</li> </ul>
I/O Connector	<ul style="list-style-type: none"> <li>- 2* USB3.2 (Gen. 2)</li> <li>- 4* USB2.0</li> <li>- 2* RS232/422/485</li> <li>- 2* RS232 (option 16bit GPIO)</li> <li>- 1* HDMI</li> <li>- 1* AT/ATX Mode Button</li> <li>- 2* RJ45 (1* Intel® I225-V 2.5GbE, 1* Intel® I219LM GbE)</li> <li>- 1* 12~36V DC-in Locking Jack</li> <li>- 1* Power button</li> <li>- 1* 2pin Front Power button</li> </ul>

Power Input	<ul style="list-style-type: none"><li>- 12~36V DC-in</li><li>- AC version: 100~240V AC-DC 90W power adapter or</li><li>- DC version: 12VDC with over current protection fuse</li></ul>
Power Consumption	<ul style="list-style-type: none"><li>- 42W</li></ul>
Dimensions	<ul style="list-style-type: none"><li>- 406.81 * 259.12 * 56.00mm</li></ul>
Compliance	<ul style="list-style-type: none"><li>- CE, FCC, option</li></ul>
Safety	<ul style="list-style-type: none"><li>- Shock: 1ms duration</li><li>- Vibration: 5~500Hz/1 Grms</li></ul>
Temperature	<ul style="list-style-type: none"><li>- Operating: : -10°C ~ 60°C</li><li>- Storage: -20°C ~ 70°C</li></ul>