



879.00 EUR

incl. 19% VAT, plus shipping

- **Intel Celeron !**
- **Multi-Touch !**
- **15" WXGA Panel Computer !**

- 15" WXGA (1024 x 768) LED Display
- Projected Capacitive Multi Touch (P-CAP)
- Aluminum Front Bezel
- Fanless Intel® Celeron® Processor J6412
- Up to 32GB DDR4-3200, 2 x Intel 2.5GbE
- HDMI-out for 2nd Display
- VESA 100mm/Panel Mount Support
- Support TPM2.0 (option)
- DC-in 12V

## SYSTEM

### PROCESSOR

Intel® Celeron® Processor J6412 (formerly Elkhart Lake) , 2.0 GHz (Quad-Core), Burst frequency 2.6GHz

### SYSTEM MEMORY

1 x DDR4 3200 Single Channel SODIMM, Non-ECC (Max.16GB, up to 3200MHz)

### ETHERNET

2 x Intel® I225-V, 2.5GbE Base-TX

STORAGE DEVICE	1 x M.2 M-key 2242/2280 (SATA) 1 x 2.5" SATA-III Drive Bay
I/O	3 x DB9 Type COM port (2 x RS-232, 1 x RS-485) 4 x USB3.2 Gen 1 2 x USB2.0 1 x HDMI2.0b (Max. Resolution: 4096 x 2160@60Hz) 2 x RJ45 10/100/1000/2500 LAN 1 x DC-in 12V Jack (Lock type) 1 x Line-out 1 x MIC 1 x Power Button
EXPANSION	1 x M.2 E-key 2230 (PCIe x1/USB2) (internal RP-SMA wires and Antenna pre-installed)
CELLULAR (5G)	—
OS SUPPORT	Windows 10 (64bit), Windows 11 (enable PTT in BIOS) Linux

## MECHANICAL

CONSTRUCTION	Aluminum Front Bezel + Metal Chassis
MOUNTING	VESA 100mm, Panel Mount
DIMENSIONS (W x H x D)	367.4 x 291.4 x 72.5mm (14.46" x 11.47" x 2.85")
CARTON DIMENSION	597 x 357 x 483mm (23.50" x 14.06" x 19.02")
GROSS WEIGHT	—

## ENVIRONMENT & CERTIFICATION

OPERATING TEMPERATURE	-10°C ~ 60°C (14°F ~ 140°F) with 0.5 m/s airflow
STORAGE TEMPERATURE	-20°C ~ 70°C (-4°F ~ 158°F)
STORAGE HUMIDITY	90% @40°C (non-condensing)
VIBRATION	1 Grms/ 5~ 500Hz/ operation
SHOCK	—
CERTIFICATION	Meet CE/FCC Class A
<b>POWER</b>	
INPUT	DC-in 12V
<b>LCD</b>	
DISPLAY TYPE	15.0" TFT-LCD, LED
MAX. RESOLUTION	1024 x 768
MAX. COLORS	16.7M colors (8 bit for R,G,B)
LUMINACE	350 cd/m <sup>2</sup>
VIEWING ANGLE	178° (H), 178° (V)
BACK LIGHT	LED
<b>TOUCH SCREEN</b>	
TYPE	P-CAP Touchscreen
LIGHT TRANSMISSION	85%