



999.00 EUR

incl. 19% VAT, plus shipping

- **For Celeron-M/Pentium-M**
- **Integr. Autostart Controller**
- **Integr. Automotive power**
- **Dualchannel VGA**

Support: [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#) | [Dual-Out-HowTo \[EN\]](#)

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller.

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

CALU specifications

Processor (supported)

Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher

Memory

Supports DDR 333/266 DIMM RAM
0.8" low profile
2x memory slots !
Maximum : 2 GB

Video

Intel Extreme Graphics 2
Supports up to 64MB DVMT video memory

Audio

Software AC '97 Audio CODEC

Peripheral Connection

Front :

1 x IEEE 1394 Firewire port

1 x USB 2.0 / 1.1 Port

1 x MIC Port

1 x Ear Phone output Jack

Power-on button

Reset button

Power-on and HDD LED

Rear :

1 x RS232 COM port

1 x RJ45 10/100Mb Fast Ethernet

1 x Line-Out output Jack

2 x USB 2.0 / 1.1 Ports

1 x 15 pin VGA

1 x DVI

Storage

One 2.5 inch Hard Disk and 9.5mm high.
(Support Ultra DMA 33/66/100).

Weight & Size

System approximately 3kg (fully equipped).

System Dimension: 155 x 255 x 55 mm

9-16V, 5A

Power req.

Accessory

Storage

Supports all Standard Slim CD-ROM/DVD-ROM,
CD-RW, DVD-RW Combo

Supports all 2.5" standard IDE hard drive,
ATA-100/66/33.

Scope of supply

Connector cable for Plus, ignition plus and
ground

Barebone

CPU Kühlkörper

Installation Tutorial : [Support / Manuals](#)

Graphics driver for 800x480 resolution : [Here](#)