

489.00 EUR

incl. 19% VAT, plus shipping



- **Barebone !**
- **Intel N97 !**
- **2x LAN !**
- **3 Display support !**

- Powered by Intel® N97 SoC Processor (formerly Alder Lake)
- High-Performance Memory: Supports DDR5 SO-DIMM
- 4K Display: Supports DP Alt Mode
- Storage & Expansion: 1 x M.2 E-Key, 1 x M Key
- Enhanced Security: TPM 2.0
- Dual 2.5GbE Ports for Reliable and High-Speed Networking Connections

SYSTEM

MB FORM FACTOR

CPU

CHIPSET

MEMORY

BIOS

WAKE ON LAN

WATCHDOG TIMER

SECURITY

RTC BATTERY

OS SUPPORT

POWER

POWER REQUIREMENT

POWER ON MODE

NUC

Onboard Intel® Processor N97 (Formerly Alder Lake-N, TDP 12W)

Intel® SoC

1 x DDR5 4800MHz, Single Channel SO-DIMM, up to 32GB

UEFI

Yes

255 Levels

TPM2.0 (dTPM, Optional)

Lithium Battery

Windows® 11 (64bit)

Windows® 10 (64bit)

Linux

DC-in 12-19V

60W Adapter: AC90~240V, DC12V/5.0A

AT / ATX (Default) Mode

DISPLAY
GPU
DP/HDMI

Intel® UHD Graphics

2 x Type C DP1.4 (Max Resolution: 4096 x 2160@60Hz)

1 x DP1.4 (Max Resolution: 4096 x 2160@60Hz)

1 x HDMI 2.0 (Max Resolution: 4096 x 2160@60Hz)

Support 3 Displays

AUDIO
CODEC
LAN
ETHERNET
SYSTEM I/O
REAR PANEL I/O

Realtek Audio Codec

2 x RJ45 for Intel® I226-V 2.5GbE

2 x RJ45
1 x HDMI 2.0
1 x DP 1.4
2 x USB 3.2 Gen 2
1 x DC-in (Lockable)
2 x WIFI Antenna Holes (Optional)
1 x GND Hold

FRONT PANEL I/O

1 x Power Button
2 x USB 3.2 Type C support DP ALT mode
1 x Combo Audio (Line out & Mic)
1 x RS-232/422/485

EXPANSION
M.2

1 x M-Key 2260/2280 (PCIe 3.0 x2/SATA III)
Support NVMe
1 x E-Key 2230 (USB 2.0/PCIe 3.0 x1) Support CNVio

MECHANICAL
MOUNTING
DIMENSIONS (W x D x H)
NET WEIGHT

Wall + VESA mount
129.0 (W) x 109.4 (D) x 34.0 (H) mm
0.56 KG

ENVIRONMENT & CERTIFICATION
OPERATING TEMPERATURE
CERTIFICATION

-20°C ~ 60°C (-4°F ~ 140°F)
CE/FCC Class A
LVD

ESG DECLARATION

China RoHS
CMRT Report
TSCA Declaration
WEEE
REACH