



398.00 EUR

incl. 19% VAT, plus shipping

- 4x Gigabit LAN !
- 2x SFP+ 10Gbps !
- Metal enclosure !
- 5G Modem support !



Support:  [Specifications](#)

- Intel® Pentium Processor N150
- 1x SO-DIMM DDR4 Slot (32GB Max.)
- 4x GbE LAN ports (Intel I211)
- 2x SFP, 10Gbps Intel 82599ES
- 1x HDMI 2.1 Port / 1 x dP 1.4
- 1x NVMe SSD slot
- 1x M.2 for 4G/5G module (SIM card slot available)

Tested with a.o. Quectel RM530N-GL 5G modem card.

Parameter	Specification
CPU	Intel® Processor N150 0.8–3.6 GHz
Cores / Threads	4 Cores / 4 Threads
Cache	6 MB Intel® Smart Cache
TDP	6 W
Architecture	Products formerly Twin Lake
Memory	SO-DIMM DDR4 slot × 1, max 16 GB
Storage	SSD (M.2 2280 SATA / NVMe), no HDD expansion
Audio	HD Audio Realtek ALC897
Graphics	Intel® UHD Graphics
Network	10/100/1000/2500BASE-T Ethernet (RJ45) × 4 (Intel I226V); 82599ES SFP+ × 2

Extendable Slots	M.2 E KEY 2230 × 1 (Wi-Fi / Bluetooth / Wi-Fi 6 module); M.2 B KEY 3042/3052 × 1 (4G / 5G module with SIM slot)
OS Support	Windows 10, Windows 11, Ubuntu 24.04, CentOS 9
BIOS Functions	AC Power Recovery, UEFI PXE Boot, Wake-on-LAN, Scheduled Power On/Off
Virtualization	Intel VT-x, VT-d supported; No Hyper-Threading
Working Environment	-10 ~ 60 °C; 0 – 95 % RH (no condensation)
Working Voltage	DC 12 V / 5 A
Static Electricity	Contact discharge 2 kV, Air discharge 6 kV
Storage Environment	-10 ~ 60 °C; 0 – 95 % RH (no condensation)
I/O Ports	USB 3.0 × 1, USB 2.0 × 5, HDMI 2.1 × 1, DP 1.4 × 1, LAN × 4, SFP+ × 2, USB Type-C × 1, DC-IN 12 V × 1, ATX Self-Power-On × 1, 3.5 mm Audio Combo × 1, RJ45 RS-232 × 1, BIOS Reset Button × 1
Built-in Socket	FP_USB1 × 1, FP 8 PIN × 1, TPM 14 PIN × 1, CPU FAN1 × 1, SPK_CON 4 PIN × 1, GPIO 10 PIN × 1, ESPI_DEBUG 10 PIN × 1, M2B_PWR1 3 PIN × 1, JBAT 2 PIN × 1, BATCON × 1, SYS_FAN1 4 PIN × 1, PW_IN 2 PIN Power Terminal
Display Mode	Dual Display (HDMI 2.1 + DP 1.4), Copy or Extended Mode; Max Resolution (HDMI 2.1): 4096 × 2304 @ 60 Hz; Max Resolution (DP 1.4): 4096 × 2304 @ 60 Hz
Dimensions / Weight	197.4 × 126.3 × 47.5 mm; 1.2 kg (net), 1.8 kg (gross)
Material / Features	Aluminum alloy case, patented compact design, supports 7 × 24 operation
Cooling	Passive (natural heat dissipation)
Bracket Options	Dedicated Bracket; Supports VESA, optional Ear Mount / DIN Bracket
Packing Box	Kraft Paper Box and Anti-Shock Corrugated Carton
Packing List	1x Barebone, 1x Power Cable (EU), 1x AC/DC Power Adapter, 1x Screws Bag 1x QA Card, 1x User Manual, 1x VESA Bracket