

139.00 EUR

incl. 19% VAT, plus shipping



- **Mini-PCIe !**
- **5G / LTE !**
- **Global !**
- **RG255C-GL !**

Quectel RG255C-GL Mini PCIe is a 5G RedCap module adopting standard PCI Express® Mini Card form factor (Mini PCIe). Adopting the 3GPP Rel-17 RedCap technology, the module supports 5G LAN*/ Slicing/ URLLC, etc., with a theoretical peak data rate of 223 Mbps in the downlink and 123 Mbps in the uplink. The module supports LTE Cat 4 and 5G Sub-6 SA modes , and is backward compatible with 3GPP Rel-15 and Rel-16 networks. The module can meet customers' different application demands for medium speed, large capacity, low latency, high reliability, etc.

RG255C-GL Mini PCIe module supports Qualcomm® IZat™ location technology Gen 9VT (GPS, GLONASS, NavIC, BDS and Galileo). The integrated GNSS receiver greatly simplifies product design and provides quicker, more accurate and more dependable positioning capability.

A rich set of Internet protocols, industry-standard interfaces (USB 2.0, PCM, UART, etc.) and abundant functionalities (USB drivers for Windows 8.1/ 10/ 11, Linux and Android) extend the applicability of the module to a wide range of RedCap applications.

- Worldwide 5G/ 4G coverage
- 5G SA mode, 5G LAN*/ URLLC/ Slicing supported
- Multi-constellation GNSS receiver available for applications
- requiring fast and accurate fixes in any environment (optional)
- Feature refinements: DFOTA and VoNR/ VoLTE (optional)

| | |
|-------------|--|
| Region | Global |
| FORM FACTOR | PCIe / 30.0 × 50.95 × 4.95 /11g weight |

| | |
|------------------------------|--|
| 5G BANDS (Global) | 5G NR: 3GPP Release 17 RedCap SA operation, Sub-6 GHz 5G NR SA: n1/ 2/ 3/ 5/ 7/ 8/ 12/ 13/ 14/ 18/ 20/ 25/ 26/ 28/ 30/ 38/ 40/ 41/ 48/ 66/ 70/ 71/ 77/ 78/ 79 DL 2x2 MIMO: n1/ 2/ 3/ 5/ 7/ 8/ 12/ 13/ 14/ 18/ 20/ 25/ 26/ 28/ 30/ 38/ 40/ 41/ 48/ 66/ 70/ 71/ 77/ 78/ 79 |
| LTE | LTE-FDD: B1/ 2/ 3/ 4/ 5/ 7/ 8/ 12/ 13/ 14/ 17/ 18/ 19/ 20/ 25/ 26/ 28/ 30/ 66/ 70/ 71 LTE-TDD: B34/ 38/ 39/ 40/ 41/ 42/ 43/ 48 DL 2 × 2 MIMO: B1/ 2/ 3/ 4/ 5/ 7/ 8/ 12/ 13/ 14/ 17/ 18/ 19/ 20/ 25/ 26/ 28/ 30/ 34/ 38/ 39/ 40/ 41/ 42/ 43/ 48/ 66/ 70/ 71 |
| Operating temperature | -30°C - 75°C Extended: -40 ~ +85°C |
| Data transmission (Max.) | 5G SA Sub-6: 223 Mbps (DL)/ 123 Mbps (UL) LTE: 195 Mbps (DL)/ 105 Mbps (UL) |
| Interfaces | (U)SIM: x1 UART: x2 USB: 2.0: x1 PCM: x1 I2C: x1 Antennas: Cellular: x2, GNSS: x1 |
| Enhanced features | Digital Audio and VoNR/VoLTE (optional) DTMF: Dual-tone Multi-frequency DFOTA: Delta Firmware over the Air (U)SIM Card Detection |
| Electrical features | Supply Voltage Range: 3.0–3.6 V, typ. 3.3 V Power Consumption: TBD |
| Drivers: | Windows 8.1/10/11; Linux 2.6–6.7; Android 4.x–12.x |
| Certifications | CE/ RCM / FCC/ IC / RoHS |