

49.00 EUR

incl. 19% VAT, plus shipping



- **Norvi X Series !**
- **4x Relay Output !**
- **Extension !**

**Support:**  [Specifications](#)

- 4 × Electromechanical relay outputs (COM / NO)
- Controlled via PCA9538 I<sup>2</sup>C I/O expander
- Industrial relay with high endurance
- Suitable for AC and DC load switching
- Compact DIN-rail compatible expansion module
- Designed for NORVI X modular architecture

The NORVI X-R4 is a 4-channel relay output expansion module designed for the NORVI X modular controller platform. It provides electrically isolated relay outputs suitable for industrial control, automation, and power switching applications.

Relay outputs are controlled via an I<sup>2</sup>C I/O expander (PCA9538), allowing reliable expansion with minimal MCU I/O usage.

Range of product  
Product type /  
Model

NORVI X  
Expansion Module f. NORVI X Series  
NORVI X-R4

Certifications	EN 61131-2:2007 EN 61010-1:2010+A1:2019 EN IEC 61010-2-201:2018 2014/30/EU- Electromagnetic Compatibility (EMC) Annex III, Part B, Module C
Dimensions	81 x 104 x 23 mm
Mounting	DIN RAIL
Terminal Type	Push-in terminal
Environment	<b>IP20</b> Operating altitude: 0-2000 meters Operating Temperature: -10 ... - +85°C Shock resistance: 15 gn for 11ms Resistance to electrostatic discharge: 4kV on contact / 8kV on air
Supply Voltage (V)	24V / 80mA
<b>I/O Specification</b>	
Number of Outputs	4x SPST Relays Outputs
Output Type	Single Pole Normally Open Relay
Insulation System	Class F IEC 61810 Standard
Rated Switching Voltage	250 VAC / 30 VDC
Maximum Switching Voltage	277 VAC / 5 A
Breaking Capacity (Max)	1250 VA (AC)   750 W (DC)
Contact Material	AgNi, gold-plated
Initial Contact Resistance	< 30 mΩ (5 VDC, 100 mA)
Mechanical Endurance	10 × 10 <sup>6</sup> operations
Power Supply	24 V DC (shared with CPU via expansion port)
Communication	Direct GPIO / Internal Expansion Bus Push-in Terminal Block