

149.00 EUR

incl. 19% VAT, plus shipping



- **DDR-II !**
- **FANLESS !**
- **1.2 Ghz !**
- **6W !**

This board is based on the latest VIA C7 architecture.

### **J7F2EDEN12G Specifications**

<b>Processor</b>	VIA C7 1.2 GHz processor
<b>Chipset</b>	VIA CN700 north bridge VIA VT8237R south bridge
<b>System Memory</b>	1 DDR2 400/533 DIMM Up to 1GB memory size
<b>VGA</b>	Integrated VIA UniChrome AGP graphics
<b>Expansion Slots</b>	1 PCI
<b>Onboard IDE</b>	4 Ultra DMA 133
<b>Onboard Serial ATA</b>	2 SATA connectors
<b>Onboard Floppy</b>	1 Floppy Port
<b>Onboard USB</b>	8 USB 2.0
<b>Onboard LAN</b>	VIA 6103 10/100
<b>Onboard Audio</b>	ALC655 6 channel AC'97 codec
<b>Onboard TV Out</b>	VIA VT1622A TV encoder
<b>Onboard 1394</b>	IEEE 1394
<b>Back Panel I/O</b>	1 1394 1 RCA video 1 VGA port 2 USB 2.0 1 LAN port 2 IEEE 1394 ports 1 serial ports 1 PS2 mouse port 1 PS2 keyboard port 3 audio jacks: line-out, line-in, and mic-in

**Onboard I/O Connectors**

3 USB 2.0 connectors for 6 USB ports  
1 parallel port  
1 VGA port  
2 serial ports  
1 PS2 keyboard connector  
1 PS2 mouse connector  
1 floppy port  
Line-in/out/MIC audio ports

**BIOS**

Award BIOS LPC 4Mbit Flash memory

**System Monitoring & Management**

CPU temperature  
Modem ring wake up  
RTC Alarm  
Keyboard power on  
System temperature  
System voltage  
Fan speed

**Operating Humidity**

0% ~ 95% (relative humidity; non-condensing)

**Form Factor**

Mini-ITX (17cm x 17cm)

**Includes**

ATA 133 flat cable (40 wire, 80 conductor, 3 connectors)

CD

SATA Cable

Floppy Cable