



429.00 EUR

incl. 19% VAT, plus shipping

- For Celeron-M/Pentium-M
- Integr. Automotive PSU
- Dualchannel VGA
- PCMCIA

CARTFT.COM

**Support:**  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#) |  [Dual-Out-HowTo \[EN\]](#)

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller.

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !  
As an additional highlight this barebone offers a PCMCIA slot.

## CALU specifications

### Processor (supported)

Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher

### Memory

Supports DDR 400/333/266 DIMM RAM  
0.8" low profile  
2x memory slots !  
Maximum : 2 GB

### Video

Intel Extreme Graphics 2  
Supports up to 64MB DVMT video memory

### Audio

Software AC '97 Audio CODEC

## Peripheral Connection

### Front :

1 x PCMCIA Slot  
1 x IEEE 1394 Firewire port  
1 x MIC Port  
1 x Ear Phone output Jack  
Power-on button  
Reset button  
Power-on and HDD LED

### Rear :

1 x RS232 COM port  
1 x RJ45 10/100Mb Fast Ethernet  
1 x Line-Out output Jack  
2 x USB 2.0 / 1.1 Ports  
1 x 15 pin VGA  
1 x DVI

## Storage

One 2.5 inch Hard Disk and 9.5mm high.  
(Support Ultra DMA 33/66/100).

## Weight & Size

System approximately 3kg (fully equipped).  
System Dimension: 155 x 255 x 55 mm  
9-16V, 5A

## Power req.

## Accessory

## Storage

Supports all 2.5" standard IDE hard drive,  
ATA-100/66/33.

## Scope of supply

Connector cable for Plus, ignition plus and  
ground  
Barebone  
CPU Kühlkörper

Installation Tutorial : [Support / Manuals](#)

Graphics driver for 800x480 resolution : [Here](#)