



CARTFT.COM

389.00 EUR

incl. 19% VAT, plus shipping

- **12VDC based !**
- **4x LAN ports**

Support:  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#)

CarPC-barebone for use with Intel Pentium-M/Celeron-M CPU.

CALU specifications

Processor (supported)

Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher

Memory

Supports DDR 400/333/266 DIMM RAM
0.8" low profile
2x memory slots !
Maximum : 2 GB

Video

Intel Extreme Graphics 2
Supports up to 64MB DVMT video memory

Audio

Software AC '97 Audio CODEC

Peripheral Connection

Front :

3 x RJ45 10/100Mb Fast Ethernet
1 x IEEE 1394 Firewire port
1 x USB 2.0 / 1.1 Port
1 x MIC Port
1 x Ear Phone output Jack
Power-on button
Reset button
Power-on and HDD LED

Rear :

1 x RS232 COM port
1 x parallel printer port
1 x RJ45 10/100Mb Fast Ethernet
1 x Line-Out output Jack
2 x USB 2.0 / 1.1 Ports
1 x 15 pin VGA
1 x 12v DC Power Jack input

Storage

One 2.5 inch Hard Disk and 9.5mm high.
(Support Ultra DMA 33/66/100).

Weight & Size

System approximately 3kg (fully equipped).
System Dimension: 155 x 255 x 55 mm
12V, 5A

Power req.

Accessory

Storage

Supports all Standard Slim CD-ROM/DVD-ROM,
CD-RW, DVD-RW Combo
Supports all 2.5" standard IDE hard drive,
ATA-100/66/33.

Scope of supply

110V/230V EU power supply
Barebone
CPU Kühlkörper

Graphics driver for 800x480 resolution : [Here](#)