



149.00 EUR

incl. 19% VAT, plus shipping

- **VIA C7 NanoBGA CPU**
- **2.0 Ghz !**
- **DDR-II !**
- **20W**

This board is based on the latest VIA C7 architecture.

### **7F2WE-2G-OC Specifications**

#### **Processor**

VIA C7 2.0 GHz processor

#### **Chipset**

VIA CN700 north bridge

VIA VT8237R south bridge

#### **System Memory**

1 DDR2 400/533 DIMM

Up to 1GB memory size

#### **VGA**

Integrated VIA UniChrome AGP graphics

#### **Expansion Slots**

1 PCI

#### **Onboard IDE**

4 Ultra DMA 133

#### **Onboard Serial ATA**

2 SATA connectors

#### **Onboard Floppy**

1 Floppy Port

#### **Onboard USB**

8 USB 2.0

#### **Onboard LAN**

VIA 6103 10/100

#### **Onboard Audio**

ALC655 6 channel AC'97 codec

#### **Onboard TV Out**

VIA VT1622A TV encoder

#### **Onboard 1394**

IEEE 1394

<b>Back Panel I/O</b>	<ul style="list-style-type: none"> <li>1 1394</li> <li>1 RCA video</li> <li>1 VGA port</li> <li>2 USB 2.0</li> <li>1 LAN port</li> <li>2 IEEE 1394 ports</li> <li>1 serial ports</li> <li>1 PS2 mouse port</li> <li>1 PS2 keyboard port</li> </ul>
<b>Onboard I/O Connectors</b>	<ul style="list-style-type: none"> <li>3 audio jacks: line-out, line-in, and mic-in</li> <li>3 USB 2.0 connectors for 6 USB ports</li> <li>1 parallel port</li> <li>1 VGA port</li> <li>2 serial ports</li> <li>1 PS2 keyboard connector</li> <li>1 PS2 mouse connector</li> <li>1 floppy port</li> <li>Line-in/out/MIC audio ports</li> </ul>
<b>BIOS</b>	Award BIOS LPC 4Mbit Flash memory
<b>System Monitoring &amp; Management</b>	<ul style="list-style-type: none"> <li>CPU temperature</li> <li>Modem ring wake up</li> <li>RTC Alarm</li> <li>Keyboard power on</li> <li>System temperature</li> <li>System voltage</li> <li>Fan speed</li> </ul>
<b>Operating Humidity</b>	0% ~ 95% (relative humidity; non-condensing)
<b>Form Factor</b>	Mini-ITX (17cm x 17cm)
<b>Includes</b>	<ul style="list-style-type: none"> <li>ATA 133 flat cable (40 wire, 80 conductor, 3 connectors)</li> <li>CD</li> <li>SATA Cable</li> <li>Floppy Cable</li> </ul>