



CARTFT.COM
Shop for mobile
PC- and GPS-Solutions

CALUCORE-M-DVI - Core2Duo Car-PC Barebone *FANLESS* --DualChannel
(DVI+DSUB)-- [new]

[<http://www.cartft.com/catalog/il/781>]



398.00 EUR

incl. 19% VAT, plus shipping

- FANLESS carpc system
- Core2Duo
- Dualchannel VGA
- Intel 945 chipset

CARTFT.COM



Support: [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel Celeron M440 CPU.

CALU specifications

Processor (supported)

Support Socket 479, FSB 533MHZ, FSB 667MHZ, Intel Mobil CPU (Celeron M 410, 420, 430, 440 & 450 CPU, Core Duo T2300, T2400, T2500, T2600 & T2700 CPU, Core 2 Duo T5500, T5600, T7200, T7400 & T7600 CPU).

Memory

Support 1x SO-DDR-II RAM

Chipset

Intel Intel 945GM / ICH 7M

Video

Intel Graphics Media Accelerator 950

Audio

Software AC '97 Audio CODEC

Peripheral Connection

Front :

1 x IEEE 1394 Firewire port

1 x USB 2.0 / 1.1 Port

1 x MIC Port

1 x Ear Phone output Jack

Power-on button

Reset button

Power-on and HDD LED

Rear :

1 x RS232 COM port

1 x RJ45 10/100/1000 Mbit Fast Ethernet

1 x Line-Out output Jack

2 x USB 2.0 / 1.1 Ports

1 x 15 pin VGA

1 x DVI

1 x TV-Out

1 x 12v DC Power Jack input

Storage

One 2.5 inch SATA Hard Disk
(Support Ultra DMA 33/66/100).

Weight & Size

System approximately 3kg (fully equipped).

System Dimension: 155 x 255 x 55 mm

12V, 5A

Power req.**Accessory****Storage**

Supports all Standard Slim CD-ROM/DVD-ROM,
CD-RW, DVD-RW Combo

Supports all 2.5" SATA IDE hard drive,
ATA-100/66/33.

Scope of supply

110V/230V EU power supply

Barebone

CPU Kühlkörper

Graphics driver for 800x480 resolution : [Here](#)