



198.00 EUR

incl. 19% VAT, plus shipping

- **1x Mini-PCI**
- **Dual LAN !**
- **Compact Flash !**



Model	• VIA EPIA SN18000G
Processor	• VIA C7 1.8GHz
Chipset	• VIA CN896 North Bridge • VIA VT8251 South Bridge
System Memory	• 2 DDR2 400/533/667 DIMM sockets • Up to 4GB Memory Support
VGA	• Integrated VIA Chrome9™ HC Graphics Video acceleration
Expansion Slots	• 1 16-Lane PCI-E slot • 1 32-Bit miniPCI slot
Onboard IDE	• 1 UltraDMA 133/100/66 connector
Onboard LAN	• 1 VIA VT6103L 10/100Mbps Ethernet PHY • 1 VIA VT6130 PCI-E Gigabit Ethernet Controller
Onboard Audio	• VIA VT1708A High Definition Audio Codec
Onboard TPM	• Infineon SLB9635TT 1.2 (Trusted Platform Module)
Onboard I/O Connectors	• 4 SATA II connectors • 2 Fan pin connectors: CPU/Sys FAN • 1 USB pin connectors for 2 additional USB 2.0 ports • 1 LVDS/TTL/DVI module connectors(an add-on card is required) • 1 CF(compact Flash) type I connector(share with IDE1)

- 1 serial port pin connector for COM2 (5V/12V selectable)
- 1 LPC header
- 1 CIR pin connector(switchable for KB/MS)
- 1 SIR pin connector (IRDA 1.0)
- 1 SMBUS connector
- 1 Digital I/O pin connector
- 1 S/PDIF out pin connector
- 1 Front-panel pin connector
- 1 Front-panel audio pin connectors(MIC and Line-out)
- ATX power connector

Back Panel I/O

- 1 PS2 mouse port
- 1 PS2 keyboard port
- 1 Serial port
- 1 VGA port
- 2 RJ-45 LAN connector
- 4 USB 2.0 ports
- 3 Audio jacks for MIC-In, Line-In & Line-Out (5.1 Support)

BIOS

- AMI BIOS
- LPC 4/8Mbit flash memory

Operating System Management

- Windows 2000/XP, Linux, Win CE, XPe
- Fan control
- CPU voltage monitoring
- AC power failure recovery
- System power management
- Wake-on-LAN, Keyboard-power-on, Timer-Power-on,
- Watch-Dog Timer,

Operating Temperature

0°C ~ 50°C

Operating Humidity

0% ~ 95% (relative humidity; non-condensing)

Form Factor

- Mini-ITX(6 layers)
 - 17cm x 17cm
-