



999.00 EUR

incl. 19% VAT, plus shipping

- **Fanless !**
- **1GB RAM !**
- **1.2 Ghz !**



Support:  [HDD-Installation \[DE\]](#) |  [HDD-Installation \[EN\]](#) | [Drivers \(Win\)](#) | [Graphics Driver \(Win\)](#)

Fanless PC-Barebone. For a full-featured PC you only need to add one 2.5" PATA harddrive.

Because of its size (170 x 123 x 56 mm !) the system is perfect for these applications :

- POS
- Digital Signage
- Kiosk

Or use as attractive office-computer or server.

CPU	VIA Eden Esther 1.2GHz processor
BIOS	AMI BIOS
System Chipset	VIA CX700M
I/O Chip	VT1211
System Memory	Onboard 1024MB DDR2
MIO	1xEIDE(UltraDMA 133),1x PS/2 K/B,1x P/S2
	Mouse
PRT	1x Printer port

RS232	2x RS-232 port
USB	2 X USB 2.0 Ports (one at front)
Output	VGA
Display Chipset	Integrated VIA UniChrome Pro II,2D/3D Graphics with MPEG4 and WMV9 decoding accelerator
Display Memory	Up to 128MB share system memory
Display Resolution	Up to 1920 x 1440
Audio AC97 2.2(Codec)	VIA Vinyl VT1708
Audio Interface	Line Out, Mic In
Ethernet Chipset	Realtek RTL8100B 10/100 Base-T Ethernet
Ethernet Remote Boot ROM	built-in boot ROM function (PXE Supported)
2.5" Hard Disk installation support	YES
Power Requirement	+5V@4A
Operating Temp	0 ~ 60°C (32-140 °F)
Operating Humidity	0% - 90% relative humidity, non-condensing
Size (W x H x D)	170 x 123 x 56 mm
Weight	970g
Certification	CE,FCC